


Status of SuperNEMO

ISOTTA meeting, 1-2 December 2014

The SuperNEMO detector



same detection technique as NEMO-3 :

- full reconstruction of the topology of the event [tracks of charged particle (and sign of charge) measured by the tracker + energy and time measured by the calorimeter]
- measurement of his backgrounds in independent channels with higher statistics than $\beta\beta$

From NEMO-3 to SuperNEMO



	NEMO-3	SuperNEMO
Mass	6.9 kg	100 kg
Isotopes	^{100}Mo 7 isotopes	^{82}Se ^{150}Nd , ^{48}Ca
Energy resolution (σ FWHM) @ 3 MeV	3.4 8 %	1.7 4 %
Radon in tracker $\mathcal{A}(^{222}\text{Rn})$	5.0 mBq/m ³	0.15 mBq/m ³
Sources contaminations $\mathcal{A}(^{208}\text{Tl})$ $\mathcal{A}(^{214}\text{Bi})$	$\sim 100 \mu\text{Bq/kg}$ 60 - 300 $\mu\text{Bq/kg}$	$< 2 \mu\text{Bq/kg}$ $< 10 \mu\text{Bq/kg}$
Total background cts $\cdot\text{keV}^{-1}\cdot\text{kg}^{-1}\cdot\text{y}^{-1}$	1.3×10^{-3}	5×10^{-5}
Sensitivity (90 % CL) $\mathcal{T}_{1/2}^{0\nu}$ $\langle m_\nu \rangle$	$> 1.1 \times 10^{24} \text{ y}$ $< 0.33 - 0.87 \text{ eV}$	$> 1 \times 10^{26} \text{ y}$ $< 0.04 - 0.10 \text{ eV}$

SuperNEMO Demonstrator Goals

[1st module, ~7 kg of source]

- ▶ SuperNEMO demonstrator module construction started in 2012


- ▶ NEMO-3 sensitivity in only 5 months (90 % CL):

$$\mathcal{T}_{1/2}^{0\nu} > 1.1 \times 10^{24} \text{ y} \rightarrow \langle m_\nu \rangle < 0.33 - 0.87 \text{ eV}$$

- ▶ No background in the $0\nu 2\beta$ region in 2.5 years for 7 kg of ^{82}Se

- ▶ Sensitivity after 17.5 kg·y exposure (90 % CL):



$$\mathcal{T}_{1/2}^{0\nu} > 6.5 \times 10^{24} \text{ y} \rightarrow \langle m_\nu \rangle < 0.20 - 0.40 \text{ eV}$$



- ▶ Commissioning and

data taking expected end of 2015

Replacing NEMO-3 in the actual LSM





SuperNEMO Demonstrator Construction Status

Calorimeter


- ▶ Optical modules: 5" under assembly and 8" modules under production
- ▶ FE digitizer boards built, control and trigger boards under development
- ▶ Magnetic shields produced and mechanical structure under construction

256 × 256 × 194 mm³



Tracker

- ▶ Automated drift cells production ongoing with the wiring robot
- ▶ First 1/4 tracker C0 has been tested for radon emanation
- ▶ Cells population of C0 has reached its nominal rate: 144 cells installed







Sources

- ▶ Already 5.56 kg of enriched ⁸²Se and 4.56 kg purified
- ▶ Foils materials (glue, films...) under HPGe and BiPo selection processes
- ▶ Calibration sources deployment system and light injection under test

CALORIMETER [France]



256 × 256 × 194 mm³




Unique characterisation tools

➤ 2 electron beam spectrometers to qualify the optical modules

- Mono-energetic electron beam from a ^{90}Sr 370 MBq β source
 - $\sigma_{x,y} \approx 3 \text{ mm}$
 - Energy range [0.4-2.0] MeV
 - **FWHM @ 1 MeV = $1.0 \pm 0.2 \%$**
- Automated X/Y scanning [2 m x 1 m]



And a fine tuned optical simulations based on GEANT4




Uniformity of scintillator response



Polystyrene scintillator

- 10 L volume
- 10 000 γ /MeV
- Highly uniform Light Yield






PMTs characteristics

HAMAMATSU
HAMAMATSU PHOTONICS K.K. Electron Tube Division


New 8" PMT (R5912-03 mod02)

- 8 stages $\rightarrow G = 2.10^5 - 10^6$
- QE > 30 % @ 420 nm
- High uniformity




Optical modules energy resolution

Gain linearity



Energy resolution @ 1 MeV


1.0 MeV spectrum



Entries	26801
Mean	0.9245
RMS	0.2303
χ^2 / ndf	248.4 / 222
Constant	144.5 ± 1.3
Mean	0.9983 ± 0.0003
Sigma	0.03548 ± 0.00029




7.8 % FWHM @ 1 MeV

Energy resolution dependency





SuperNEMO Calorimeter Improvement

- ▶ Energy resolution of 7 % FWHM at 1 MeV achieved:
 - ▶ High QE large 8" PMTs (Hamamatsu R5912) directly coupled to the scintillator (no light guide) and improved HV divider
 - ▶ PVT plastic scintillators (also 8 % achieved for PS)
 - ▶ Optimization of the scintillator blocks geometry
 - ▶ Electronics sampling the PMT pulses ~ 2 GS/s (MatAcq/SNFEB)



1 MeV e^- spectrum



Status of the calorimeter

5 inches

70/80 OM [scintillators + PMTs] produced

70/80 characterized

40/80 in the magnetic shields


8 inches

40/460 scintillators already produced (arrived in CENBG)

400/460 PMTs already produced (arrived in CENBG)

6/460 OM produced (scintillators + PMTs)

MW SCHEDULE





Calorimeter radon : PMTs emanation

- **PMT glass seems not emanate radon**
- Conclusion supported by
 - 30 x R6594 PMTs emanation measurement :
 $E_m(\text{CENBG}) < 2.51 \cdot 10^{-10} \text{ Bq.s}^{-1}$ (95% C.L.)
 - 5 x R6594 broken PMTs emanation measurement
 $E_m(\text{CENBG}) < 6.01 \cdot 10^{-9} \text{ Bq.s}^{-1}$ (95% C.L.)



TRACKER [UK]



- Production with the robot [weaving of the cells] + tests at Manchester
- Assembly of the tracker at MSSSL : C0 (1/4) of the tracker completed, in commissioning
- Planning of installation at LSM

Tracker construction – Reminder of the procedure



Manchester

- Produce cassettes of 18 tracker cells
- Test each cassette
- Transport the cassettes down to MSSL

MSSL / UCL

- Construct the tracker frame, one C-section at a time
- Populate with x-wall and veto optical modules
- Radon tests
- Insert the cassettes of cells
- Commission each C-section on the surface



Radiopurity of the tracker





cells made of pure copper, delrin and inox

all components are cleaned : ultrasonic bath in a detergent solution followed by an ultrasonic bath in distilled water


all copper parts are passivated in citric acid to prevent corrosion

Cell production

To minimise human contact with the wires, the drift cells are produced by a wiring robot at the University of Manchester, in a cleanroom environment. Cells are produced in sets of 18. Each set of 18 cells is conditioned and tested immediately after production. The testing ensures there are no self-triggering or plasma-blocking points on any wires. The conditioning is continued until a good Geiger plateau is observed on all cells.










Tests of the Geiger cells




Test of 18 cells at Manchester : very stable (and wide) plateau

cell 12 @ 1775 V (last point in the "plateau")



Cell 12 - HV 1775
 Good rate: 47.61 Hz Noise rate: 0.03 Hz
 Cathode efficiency: 0.99
 PPT efficiency: 0.97
 2-spike: 0.99 0-spike: 0.00
 Miss 1st spike: 0.00 2nd spike: 0.00


CO (1/4 of the tracker) is filled with drift cells...



TRACKER

C0 is complete


- It will now be leak-tested, radon-test and commissioned on the surface
- C1 will be built and populated while this happens
- Once C1 is populated, C0 can be moved out and delivered to LSM



To measure Radon emanation of CO

Radon Trap System designed and built at CPPM


DocDB-3117 (J. Busto)



Arrived to MSSL from Marseille
on 15-May-2014



Nitrogen Gas Measurement



Activity;

$$\text{Po214} = 20.2 \pm 12.5 \text{ } \mu\text{Bq/m}^3$$

$$\text{Po218} = 35.0 \pm 15.8 \text{ } \mu\text{Bq/m}^3$$

- Bottled nitrogen with a flow rate of 7 lpm for 20 hours.
- Expect $1.6 \pm 0.5 \text{ cpd}$ (doc-3267-v4) from trap background (flushed, then closed for 24 hours).

Gas	Source	Radon Level ($\mu\text{Bq/m}^3$)
He	Cylinder	70 – 100
N ₂	Cylinder	400 – 1000
N ₂	Boil-off	90 – 140
N ₂	J-Trap	20



A Radon emanation of the C0 (1/4 of the tracker) is possible with a sensitivity comparable to the demonstrator Radon requirement $\sim 150 \text{ } \mu\text{Bq/m}^3$

TRACKER Planning

Deliveries to LSM


C-section	Old schedule (Orsay)	New schedule
C0	March 2015	May 2015
C1	August 2015	November 2015
C2	March 2016	July 2016
C3	March 2016	July 2016

SOURCE [RUSSIA, FRANCE, USA]



- ▶ Already 5.56 kg of enriched ^{82}Se and 4.56 kg purified
- ▶ Foils materials (glue, films...) under HPGe and BiPo selection processes
- ▶ Calibration sources deployment system and light injection under test

The source geometry



very thin ($\sim 57 \text{ mg/cm}^2$) source to minimize energy loss in the foil
36 strips [2.7 m long, 13 cm wide, $\sim 200 \mu\text{m}$ thick] placed in the middle of the detector

6 calibration tubes to introduce sources with an automated source deployment,
gas contamination free [to avoid penetration of Radon]

The 2 possible source design under study


^{82}Se powder mix with PVA glue to produce a solid and uniform thin foil

MYLAR Design: Two thin layers of mylar film envelop the Se+PVA bulk.

The mylar acts as the physical bound of the foil, preventing loss of the powder. About 5-10 % of PVA is enough to glue the Se.


TULLE Design: A thin bobbinet tulle produced by warp & weft nylon monofilament is embedded in the foil.

The tulle is a lighter support w.r.t. to the Mylar inducing a lower background rate for a similar material contamination. About 10-15 % of PVA is required to glue the Se.




Foil production

The PVA glue is dissolved at 80°C in ultrapure water and mixed with powder of Selenium.



The tulle (or the mylar) is installed on a dedicated support specifically to keep the tulle fabric in place.

The Se powder mixed with the liquid PVA is poured on the support and spread uniformly. Upon drying, the foil is resistant and flexible.



Measurement of the radiopurity of the first ^{82}Se source with BiPo-3



with 74 days of data, 240 g of source (1/4 of BiPo-3):

$A(^{208}\text{Tl}) < 27 \mu\text{Bq/kg}$ (90% CL)

^{214}Bi analysis still on going : more complicated because of random coincidences

source components [mylar, tulle, ...] measured with BiPo-3

Reduce the Radon Background

- ▶ Goal: reduce the internal radon background to 0.15 mBq/m^3
- ▶ Select detector materials and protections (seals, films...)



Bordeaux emanation tank



Bratislava emanation setup



Prague permeability setup


- ▶ Measure the radon in the detector or gases and radon purification



London concentration line



Gases purification



Marseille radon adsorption

Conclusion

- goals of the demonstrator :
 - demonstrate that the extremely low background level for SuperNEMO can be reached $\sim < 5\text{-}10$ bckg events for 100 kg x 5 years
 - obtain a sensitivity in exclusion at 90%CL of
$$6.5 \times 10^{24} \text{ y in } T_{1/2}$$
$$[0.2\text{-}0.4]\text{eV in } \langle m_\nu \rangle$$
for 7 kg of ^{82}Se in 2.5 years
- planning :
 - end of 2015 : calorimeter delivered at LSM, under commissioning. $\frac{1}{2}$ of the tracker delivered to LSM. Under discussion : possible data taking without the source [commissioning of the detector, possible radon measurement ?]
 - mid-2016 : full tracker deliver. Data taking

BACKUP


Current status of NEMO-3 sources

Place of Prod.	Year of Prod.	Mass (kg)	Purchased by	Owned by	Where now	Comments (Activities in mBq/kg)
Tomsk	2005-2006	2	France	ITEP	LSM	1 kg purified by INL, now in a powder form Bi-214 < 0.9 Tl-208 < 0.5 Ru-106 < 0.8 1 kg non-purified, now in a powder form Bi-214 ~ 2.6 Tl-208 ~ 1.5 Ru-106 ~ 20.8 (in 2006)
Tomsk	2007	1.5	France	France	LSM	Purified by distillation, now in a form of pellets Bi-214 < 1.9 Tl-208 < 1.2
ECP	1995	0.96	ITEP	ITEP	ITEP	Was used in NEMO-3. In 2012 was purified by distillation then into powder at ECP. Was not measured by HPGe.
ECP	2009-2010	1.1	ITEP	ITEP	ITEP	Purified by distillation; 0.6 kg is in a form of powder (not measured) 0.5 kg is in a form of pellets : Bi-214 < 1.9 Tl-208 < 1.2
?	2014	1.5	France	JINR	→ LSM	To be purchased*
TOTAL		7.06				Purified, in powder: $1.0 + 0.96^* + 0.6^* = 2.56$ Not purified, in powder: 1.0 Purified, in pellets: $1.5 + 0.5 = 2.0$ Not purified, in pellets: 0 To be purchased: 1.5^* * Not measured by HPGe or BiPo

Present status:

Demonstrator construction started in 2012:

It will be installed at LSM in the place where NEMO-3 operated



Present status:

Demonstrator construction started in 2012:

It will be installed at LSM in the place where NEMO-3 operated



Calorimeter

Optical modules: 5" under assembly and 8" under construction

FE digitizer boards built, control and trigger boards under development

DAQ components already done or under development

Construction of the calorimeter blocks, magnetic shields and mechanical structure started



Present status:

Demonstrator construction started in 2012:

It will be installed at LSM in the place where NEMO-3 operated

Calorimeter


Tracker

Wiring robot developed for automated drift cells production

First quarter of the C0 (Tracker chamber) constructed and checked for Radon emanation (OK!)

Population of the Geiger drift cells started

Commissioning of the full C0: currently at sea-level



Present status:

Demonstrator construction started in 2012:

It will be installed at LSM in the place where NEMO-3 operated

Calorimeter

Tracker

Sources

5.5 kg of ^{82}Se available with 0.5 kg already purified

Screening of potential source components (glue, support mesh...) with HPGe and BiPo ongoing

Calibration sources deployment system prototype under test




SuperNEMO: toward the new generation

Extrapolate a well known technique:

- 100 kg of $\beta\beta$ emitter in 20 detection module
- Approach Inverted Hierarchy region

	NEMO-3	SuperNEMO
Isotope	7 kg ^{100}Mo	~ 100 kg ^{82}Se (^{150}Nd , ^{48}Ca)
Exposure	35 kg y	~ 500 kg y
Energy res.	8% @ 3 MeV	4% @ 3 MeV
^{208}Tl (source)	~ 100 $\mu\text{Bq/kg}$	< 2 $\mu\text{Bq/kg}$
^{214}Bi (source)	~ 300 $\mu\text{Bq/kg}$	< 10 $\mu\text{Bq/kg}$
Rn (in tracker)	5 mBq/m ³	0.15 mBq/m ³
$T_{1/2}$	10^{24} y	10^{26} y
$\langle m_{\nu} \rangle$	0.31 - 0.79 eV	0.04 - 0.1 eV



A challenge under many aspects:

- R&D program in the past years almost completed!
- Next step: Demonstrator module

SuperNEMO: the demonstrator module

One SuperNEMO module $\rightarrow$ 7 kg ^{82}Se running ~ 2.5 y

- To be installed @ LSM (replacing NEMO-3)

Match SuperNEMO requirements



- Background level $\sim 10^{-4}$ cts./(keV kg y)
- Background free at high energy (^{150}Nd)

Reach NEMO-3 (^{100}Mo) sensitivity in 4.5 months

- Sensitivity: $\langle m_\nu \rangle \sim 0.20 - 0.40$ eV

Schedule:


- Calorimeter & tracker under production
- Installation & commissioning in 2015
- First physics data by the end of 2015!




The calorimeter [France]



Radon emanation measurement




- While a sample is emanating inside the setup the chamber (710 L) is filled with N₂ with an overpressure (~ 1.1 bar)
- Before starting the measurement the detector (70 L) is emptied
- After emanation we open the valve between the chamber and the detector and balance the pressure (1 bar)
- Since 9 % of the gas from the chamber is transferred we expect 9 % of Radon from the chamber to be transferred
- We tested this hypothesis using a ²²⁶Ra source



- Counting rate $\rightarrow$ **19.6 ± 3.2 cpd**
- Compatible with background value

Drift Cells



The tracking in the Demonstrator Module is performed by 2048 drift cells operating in Geiger mode. A central anode wire is surrounded by twelve cathode wires, in a helium-argon gas mixture. The passage of a charged particle ionises the gas, resulting in an electron avalanche. This produces a plasma that propagates along the anode wire. The time difference between the signal arriving at each end provides the longitudinal location of the charged particle.

Component cleaning



Radiopurity of all detector components is vital. Cells are made only from pure copper, steel and delrin. All components are cleaned, following a rigorous procedure: an ultrasonic bath in a detergent solution followed by an ultrasonic bath in distilled water. An automated spooling system takes the wire through the same procedure. All copper parts are then passivated in citric acid to prevent corrosion. After cleaning, all anode wire is tested before insertion into cells to check for plasma blockages or self-triggering points.