



Performance of the Reactor Neutrino Detector

Luis MANZANILLAS

manzanillas@lal.in2p3.fr

LAL-IN2P3-CNRS

On behalf of the SoLid collaboration



GDR Neutrino
APC – Paris 2018



Outlook

- Physics motivation
- The SoLid experiment
- Construction and QA
- Commissioning and calibration
- Summary








- ***Physics motivation***

Physics Motivations

● **Anomalies:** The **reactor antineutrino anomaly** and **gallium anomaly** both show discrepancies wrt expectations at $\sim 3\sigma$ level

● Oscillations into a **light sterile neutrino state** ($\Delta m^2 \sim 1 \text{ eV}^2$) could account for such deficits



● **Distortion** observed around **5 MeV** (“bump”) in the reactor **antineutrino energy spectrum**

● Hints point to ^{235}U (1609.03910, 1608.04096, 1512.06656)

● **SoLid goals:**

- RAA: Search for an **energy distortion** pattern at short baselines
- 5 MeV “bump”: Provide a **new** measurement of ^{235}U fuel **antineutrino spectrum** with a different detection technology



- ***The SoLid experiment***

SoLid goals

SoLid goals:

- Using a **different detection technology**
 - RAA: Search for an **energy and space oscillation** pattern at short baselines ([6-9] m)
 - 5 MeV “bump”: Provide a **new** measurement of ^{235}U fuel **antineutrino spectrum**

SoLid collaboration

The SoLid Collaboration

4 countries

12 institutes

~50 people




May 2017
Gent-Belgium

The BR2 site and reactor




Best fit RAA \rightarrow Oscillation length of 3-4 m for 3 MeV ν 's \Rightarrow **Compact source**

- **Compact** reactor **core** $\Phi < 50$ cm, $h = 90$ cm
 - Baselines : 6 \rightarrow 9 m
- Thermal power: 45-80 MW
- Highly **^{235}U enriched** (up to 93.5 %)
- 150 days per year duty cycle
 - Reactor off data for background estimation and subtraction
- **No nearby experiments**
- Overburden of ~ 10 mwe
- **Low background** (neutron, γ)
- **Excellent** collaboration with SCK•CEN




The SoLid technology

- Inverse beta decay: $\bar{\nu}_e + p \rightarrow e^+ + n$
- 3D highly segmented composite detector
 - 5 cm x 5 cm x 5 cm **PVT** cubes
 - $\bar{\nu}_e$ interaction
 - 2 layers / cube of **LiF:ZnS(Ag)** for neutron detection
 - Neutron capture on Li in ZnS layer :
 $n + {}^6\text{Li} \rightarrow {}^3\text{H} + \alpha + 4.78 \text{ MeV}$
 - Nuclear signals (NS) and electronic signals (ES) very different
 - \rightarrow Waveform shape discrimination (“~PSD”) + neutron trigger
- Cubes optically separated (Tyvek)
- WLS fibers + SiPM to read out signals






JINST, Vol. 12, 2017, arXiv:1703.01683



Luis MANZANILLAS

The SoLid (1600 kg) detector

- **5 Modules** of 10 planes
 - Planes of 16x16 cubes
- 4 x (fiber + SiPM + Mirror) per cube
- Automated calibration system
- Container (2.4x2.6x3.8 m) for **cooling at 5 °C**
 - Reduction of dark count rate
- **Shielding:**
 - Water wall: 50 cm thick, 3.4 m high, 28000 kg
 - Polyethylene ceiling: 50 cm thick. 6000 kg











- ***Construction and QA***

Plane construction

- ~13 000 cubes manually washed, weighted, wrapped, stacked, ...
- All cube components product information stored in database






Plane qualification with CALIPSO

- **Automated** system to place radioactive sources in front of **each cube**
 - Gamma and neutron mode
- Check **quality** and **uniformity** of the SoLid planes
 - → **Early identification of defective components**
- Gave a good **knowledge** of the detector response **before installation** at BR2
- Allowed calibration of 1 plane / day


Gamma mode

^{22}Na source with **external trigger**






Neutron mode

^{252}Cf source with **polyethylene collimator**



CALIPSO LY results

- Preliminary estimation of **LY** in all 12800 cubes
 - **Exceeds** SoLid **requirements** (40 PA/MeV \rightarrow >60 PA/MeV !)
- **Homogeneous** response
 - Can be improved with correction from attenuation length
- Minor construction **problems identified and fixed**




CALIPSO neutron results

● **^{252}Cf calibration** with PE collimator on 25 positions per plane in 3 h

- Compared to Geant4/MCNPX prediction
- Neutron **capture time** reduced to $\tau \sim 65 \mu\text{s}$ with 2 Li screens / cube and capture efficiency $\sim 66 \%$

One **bad** $^6\text{LiF:ZnS}$ **batch identified** and replaced




Only 1/12800 cubes where 1 Li **screen** was missing \rightarrow has been replaced



Cube efficiency distribution

plane 16 : Data/Monte-Carlo

Data/MC : plane 20 (corrected)



Very good neutron detection efficiency and uniformity

- 
- ***Commissioning and calibration at BR2***

Commissioning at BR2


- **First modules deployed** at BR2 last November
- **Commissioning** of the full detector **completed** beginning of February 2018
- Expected ~150 days of reactor ON data in 2018



DAQ and triggers

- **Random:** Full detector readout at 1 Hz
 - Non zero-suppressed waveforms for SiPMs monitoring
- **Threshold:** XY coincidence > 2 MeV
 - Muon and high electromagnetic event tagger
- **Neutrino:** “PSD” algorithm for neutrons
 - Past time buffer (500 μ s) & multiplane readout (+/- 3 planes)
 - \rightarrow Unbiased prompt detection

- Neutron trigger implemented in FPGA
 - Based on **peak counting**.
 - Read out long time buffer around NS: [-500 μ s, +200 μ s]





SoLid calibration goals

- Gains + crosstalk better than 1 % per channel
 - 3200 channels
- **12800 SoLid units**
 - Energy scale at 2% level
 - Neutron capture efficiency per cube at 3 % level
- Neutron capture time at the 1% level


MPPC equalization

- 99% channels operational
- Amplitude response calibrated to high quality, spread $\sim 1\%$
- Voltage scans used to calibrate individual MPPC breakdown voltages and amplification responses
- Equalize for gain response (i.e 1 PA amplitude) of 32.0 ADC/PA - equivalent to 1.8 V over-voltage




Calibrating with CROSS system

- In situ calibration
- Sits above detector planes
- Mechanically open gap between sets of ten planes (Module)
 - Source free to move in gap
 - 9 positions per gap used
 - 6 gaps in total → modules irradiated from two sides





Rails to move modules



CROSS calibration - gamma




- First calibration campaign results with ^{22}Na and AmBe
 - **100% of cubes** (w/ 4 ch) have been **calibrated** with 94 hours of data taking
 - Average of 77 PA/MeV w/o crosstalk subtraction ($\sim 13\%$) for OV of 1.5
 - Currently running at OV of 1.8 \rightarrow **LY should increase** of $\sim 15\%$ (x-talk too)



- Excellent **agreement between ^{22}Na and AmBe**
- **Confirms PVT energy linearity**
- ^{137}Cs , ^{60}Co , ^{207}Bi will be deployed in the next weeks for linearity studies + μ 's at high energy




CROSS calibration - neutron

- Calibration with AmBe (~4 MeV) and ^{252}Cf (~2 MeV)
 - Able to calibrate **n efficiency per cube** with both sources!
 - **Agreement at the ~3% level**
- Neutron reconstruction efficiency > 75%!
- Statistical error ~2.5%
 - Dominated by cubes far from the source
 - Will decrease with next calibration campaigns




Muon calibration

- Reconstruct muon tracks
 - → Edep / cube using well known dE/dx
 - Monitoring detector stability
 - Linearity at high energy



Data taking and stability

- **Stable** data taking since February → Highly stable for both reactor on and off
- **Online**, live, remote **detector monitoring**
- Online event reconstruction for subsample of data
- **Physics variables available online**



Prompt-Delayed Coincidence Candidate - 2017/12/05, 00:07:26

Online Monitoring Trending - 2018




Fig: Rates correspond to the whole detector. Each data point corresponds to one hour of data taking.




Fig: Measurements made twice per minute.








Fig: Detector channel mean. Each data point corresponds to 1 hour data taking.



First IBD like events

- Preliminary rate monitoring based on minimal cuts:
 - Timing, topology, μ veto, energy
- Significant IBD-like rate during reactor ON period
- Behaves according to what is expected
 - Spatially confined
 - Time difference consistent with thermalized n capture








- ***Expected physics results***

Expected physics results

- Baselines: 6 – 9 m
- Energy resolution 14% / \sqrt{E}
- IBD eff: 30%
- Thermal power: 60 MW
- S:B of 3:1 5 Modules
- 450 days of reactor ON



New measurement of ν spectrum of ^{235}U

On track for first physics result around the end of the year, beginning of next year

Summary

- **Construction of phase 1 (1600 kg) completed**
- **Commissioning at BR2 research reactor finished in February 2018**
- **First calibration results indicate good detector performance**
 - SiPMs equalized at the 1% level
 - LY > 60 PA/ MeV
 - Neutron trigger efficiency > 70 %
- **Data taking** in physics mode ongoing
 - ~ aiming for 150 days of reactor ON using 2018 dataset
 - + data in 2019 -2020
- SoLid observes IBD-like events
- First **physics results** expected by the end of **2018, beginning of 2019**




Thanks for your attention

Stay tuned !



BACK UP

Backgrounds



Muon induced

- Fast neutrons from spallation
- Stopping μ's (with Michel e⁻)
- Cosmogenic isotopes (e.g. ⁹Li, ⁸He)

Countermeasures:

- ✓ Shielding/underground lab
- ✓ Active veto
- ✓ Pulse Shape Discrimination (PSD)



Reactor induced

- Neutrons (fast & slow)
- γ's from n captures

Countermeasures:

- ✓ Shielding
- ✓ PSD
- ✓ **Topology**




Radioactivity

- Thorium/Uranium
- Radon/Argon
- Potassium

Countermeasures:

- ✓ Material radiopurity
- ✓ **Topology**

Backgrounds



Muon induced

- Fast neutrons from spallation
- Stopping μ 's (with Michel e^-)
- Cosmogenic isotopes (e.g. ${}^9\text{Li}$, ${}^8\text{He}$)

Countermeasures:

- ✓ Shielding/underground lab
- ✓ Active veto
- ✓ Pulse Shape Discrimination (PSD)

**MEASURED
DURING
REACTOR OFF
PERIODS**

Radioactivity







- Thorium/Uranium
- Radon/Argon
- Potassium

Countermeasures:

- ✓ Material radiopurity
- ✓ **Topology**



Quality assurance

- How to guarantee a good and homogeneous response of more than 12000 cubes?
 - → Quality assurance procedure



Neutron capture time

- Using AmBe source
- ~57% of neutrons emitted always with a 4.4 MeV γ
- Use 4.4 MeV γ to tag neutrons
- Look for a n capture on ZnS after the γ
 - Precise measurement of n capture time
 - → Comparison with MC
 - → Excellent agreement
- Validated with muon induced neutrons



Resources for calibration

- Neutron sources: AmBe (~ 4 MeV) + ^{252}Cf (~ 2 MeV)
 - Neutron rate **calibrated at the 1% level** at the National Physical Laboratory (UK)

- Gamma sources:

Source	^{22}Na	^{137}Cs	^{207}Bi	^{60}Co	n-H (AmBe/Cf)	AmBe
Energy [MeV]	2x0.511 1.27	0.667	0.57 1.064 1.77	1.17 1.33	2.2	4.44


- Muons at high energy

SoLid Calibration systems

Double calibration: **during construction** and **in-situ**


CALIPSO system

- › **Individual** plane calibration
- › Automated robot to place **radioactive sources in front of each cube**
- › Calibration during detector construction
- › Preliminary detector performance
- › **Used for quality assurance**



CROSS system

- › **Global** detector calibration
- › Automated robot to place **radioactive source between modules**
- › Calibration during reactor OFF periods
- › Detailed detector performance
- › **Energy scale + n capture efficiency per cube**






+ Muon calibration

Energy scale with ^{22}Na source

- SiPMs are **equalized** (gains) at **the 1 % level!**

- Crosscheck with data: ADC \rightarrow PA



Individual PA arrivals can be identified

SiPM response is very linear!

- The total amplitude per cube (A_{ij}) is found summing the amplitudes of the 4 SiPMs associated to each cube

$$A_{ij} = \frac{A_i^t}{g_i^t} + \frac{A_i^b}{g_i^b} + \frac{A_j^l}{g_j^l} + \frac{A_j^r}{g_j^r}$$

t,b,l,r for the position of the SiPM in the frame
 g the gain of each SiPM



Energy scale with ^{22}Na source

- No photo-peak in PVT cubes → using Compton edge

- Two independent approaches to assess the energy scale



Kolmogorov S test (KS)

Compare measured sample to a Geant4 MC sample



Analytical fit

Use pdf based on Klein-Nishina cross-section



Agreement between both methods at the 1% level!

Neutron trigger deployment

A n event using AmBe source

- Dedicated **neutron trigger** for neutrino detection.
- Based on **peak counting**.
- Combined with **large buffer** for prompt detection → high IBD efficiency.
- Deployed with CALIPSO
- **Fulfills** SoLid **requirements**
(n trigger eff > 60 %)

