Expression of Interest from French physicists to participate in the Hyper-Kamiokande experiment in Japan

Adrien Blanchet³, Sara Bolognesi¹, Margherita Buizza Avanzini², Stéphane Callier⁴, Selma Conforti Di Lorenzo⁴, Frédéric Dulucq⁴, Olivier Drapier², Jacques Dumarchez³, Sandrine Emery¹, Frank Gastaldi², Claudio Giganti³, Michel Gonin², Mathieu Guigue³, Samira Hassani¹, Christophe de La Taille⁴, Jean-Michel Lévy³, Lucile Mellet³, Thomas Mueller², Quoc Viet Nguyen³, Pascal Paganini², Boris Popov³, Benjamin Quilain², Stefano Russo³ and Marco Zito³

> ¹IRFU/DPhP Neutrino group, CEA, Saclay ²LLR Neutrino group, IN2P3/Ecole Polytechnique ³LPNHE Neutrino group, IN2P3/Sorbonne University ⁴OMEGA group, IN2P3/Ecole Polytechnique

June 2020

In this document we express strong support to the Hyper-Kamiokande experiment and review possible contributions from the French groups to the project.

1 Motivations for our participation to the Hyper-Kamiokande experiment

Hyper-Kamiokande (Hyper-K or HK) is a next generation long-baseline neutrino oscillation experiment planned to start taking data in the second half of 2020s. The main physics goal of the experiment is the discovery of CP violation in the lepton sector.

The experiment has recently been approved by the Japanese government and will be built in Japan. It will exploit the same experimental technique (Water Cherenkov detector), neutrino energy ($E_{\nu} \sim 600 \text{ MeV}$) and baseline (295 km) as the existing T2K experiment to which IN2P3 and IRFU physicists have been participating for more than 15 years.

This well-proven technology has already led to two Nobel prizes in physics with the previous detectors of the Kamiokande saga. Thanks to its larger size, HK has a sensitivity to measure CP violation at more than 5σ (3σ) for 50% (75%) of the values of δ_{CP} and will be a fundamental experiment to bring neutrino oscillation physics into the era of high precision measurements. Besides measurements of neutrino oscillations with accelerator, atmospheric and solar neutrinos, the large size of HK makes it the most sensitive experiment to rare events such as proton decay or neutrinos from supernovae explosions.

The participation of the French neutrino groups to the Hyper-Kamiokande project is built upon the human and financial investments made along the years in T2K, T2K-II,(b.q) and SK. It allowed the French groups to acquire a deep expertise and a primary role in the collaboration, thus ensuring a large return in terms of visibility and responsibility even in the very competitive environment of such large international collaborations.

HK constitutes a natural extension of the on-going activities that will allow most prominent physics outputs, notably a timely discovery of CP violation in the lepton sector and a search for rare events, such as proton decay, with unprecedented sensitivities.

Possible contributions of French groups to the HK project are briefly described in the next section and detailed in the Appendix. Let us stress that our already on-going significant involvement in the ND280 upgrade for T2K-II can be considered as a hardware contribution to the HK project.

2 Summary of the possible contributions from French groups to HK

In this section we will present a list of possible contributions to the HK experiment by the French groups. Some of these contributions (NA61/SHINE or ND280 upgrade) are based on the work done by the three groups in T2K and T2K-II.

The possible contributions to the HK far detector are discussed in the Appendix taking into account existing expertise in the different technical services of the laboratories and/or the presence of infrastructure (such as Memphyno at APC) that can be exploited for HK. Possible synergies with other activities on PMTs in France (KM3NeT or JUNO) have also been considered and will be further exploited. in the coming months.

2.1 Current manpower

The French groups have a very strong expertise being present in T2K since the beginning and having large contributions to the construction and maintenance of the near detectors and important responsabilities at analysis level. This vibrant community is distributed among IRFU, LLR and LPNHE laboratories. The approval of the HK experiment by the Japanese government (MEXT) will can potentially allow the French groups to enlarge and attract other French groups to the experiment thanks to the synergies mentioned above.

2.2 Possible contributions to HK

Table 2 summarizes the possible contributions from the French groups to the experiment. The level of possible contributions is expected to be more precisely known in 2021. Once the project is approved Following the approval of the project by the Japanese government, we will present the possible contributions to the funding agencies. Avoid repetition here!

Once Since the project is approved by the Japanese government, we could now increase and negociate our contributions with our funding agencies, considering an investment profile starting in 2020 or 2021.

2.3 Possible requests for funding from French researchers

Table 1 shows the possible timeline of the funding. To be updated!

With the final approval of the HK experiment in Japan we can now start preparation of our funding requests to the French funding agencies. The first step would be to present our potential contributions to the IN2P3 and IRFU Scientific Councils in order to get their approval. This can be done in the first part of 2021. Then the funding requests would have to be approved by the IN2P3 and IRFU directorates. Till that moment the content of this EoI would have to stay fully confidential.

Text proposed by BP. Agreed with Sara.

Source	Item	Starting year
French funding agencies	ND280 upgrade	2019
(IN2P3 & CEA)	Computing resources	2019
	HK electronics	2021
JENNIFER-II European project	T2K upgrade	2019
	HK design	2019
	mPMT development	2019
	Computing and common tools	2019
Sorbonne University	mPMT tests	2019
Ecole Polytechnique	chip design	2021?
TYL-FJPPL projects	HK R&D	2019
IRL CNRS-UoT	HK construction	2021?

Table 1: Possible fundings timeline for the French laboratories.

Far detector20-inch PMTs electronicsR&D and construction of front-end electronics 20 -inch PMTs electronicsR&D and construction of multi-PMTs with NMulti-PMTsIn-situ characterisation of multi-PMTs with NDAQ and overall electronicsR&D on clock distribution and time synchrcR&D on clock distribution and time synchrcR&D on clock distribution and time synchrcIadron production measurements with NA61/SHINEnew replica target measurements and data is new replica target measurements and data is n
20-inch PMTs electronics $R\&D$ and construction of front-end electronicsMulti-PMTsIn-situ characterisation of multi-PMTs with NMulti-PMTsIn-situ characterisation of multi-PMTs with NDAQ and overall electronics $R\&D$ on clock distribution and time synchrcAdditionalR&D on clock distribution and time synchrcAdditionalrontributionsHadron production measurements with NA61/SHINEnew replica target measurements and data aND280Electronics, mechanical engineering and DAQ fiSoftware and computingExpertise in shared computing resource
Multi-PMTsIn-situ characterisation of multi-PMTs with M $Multi-PMTs$ Test beam experiment DAQ and overall electronics $R\&D$ on clock distribution and time synchrc $Additional$ $excloration and time synchrcAdditionalexcloration and time synchrcBadron production measurements with NA61/SHINEexcloratic target measurements and data aND280ND280Electronics, mechanical engineering and DAQ fiExpertise in shared computing resourceexcloration and time resourceAdditionalexcloration and time synchrcAdditionalexcloration and time synchrcND280excloration and time synchrcAdditionalexcloration and time synchrcAdditionalexcloration and time synchrcAdditionalexcloration and time synchrcAdditionalexcloration and time synchrcA$
Matter 1 M15 Test beam experiment DAQ and overall electronics R&D on clock distribution and time synchrc Additional R&D on clock distribution and time synchrc Hadron production measurements with NA61/SHINE new replica target measurements and data a ND280 Electronics, mechanical engineering and DAQ fields Software and computing Expertise in shared computing resource
DAQ and overall electronicsR&D on clock distribution and time synchroAdditionalcontributionsHadron production measurements with NA61/SHINEnew replica target measurements and data aND280Electronics for superFGDND280Electronics, mechanical engineering and DAQ fiSoftware and computingExpertise in shared computing resource
Additional contributions Additional contributions Hadron production measurements with NA61/SHINE new replica target measurements and data a ND280 Electronics for superFGD ND280 Electronics, mechanical engineering and DAQ f Software and computing Expertise in shared computing resource
Hadron production measurements with NA61/SHINE new replica target measurements and data a ND280 Electronics for superFGD ND280 Electronics, mechanical engineering and DAQ fi Software and computing Expertise in shared computing resource
ND280 Electronics for superFGD ND280 Electronics, mechanical engineering and DAQ for Expertise in shared computing resources
Software and computing Software and computing resources and computer
Software and computing resource
Storage and CPU
and CPU

-	
	Ē
	Ð
	Ξ
•	Ξ.
	5
	õ.
	Ы.
	Ü
	വ
	ā
	نې
	0
	ĕ
	ß
	Ц
	0
•	5
	0
•	C
	Ξ
	Ξ
	8
	Ŭ.
	ਨੂ
	9
	z
	5
	Ð.
	Ξ
	-
,	Si
	. 1
	e
	Ö
	đ
ĺ	-
î	-

A Details about the possible contributions

A.1 Hadron production measurements with NA61/SHINE

The importance of dedicated hadron production measurements with the **NA61/SHINE** spectrometer at the CERN SPS for advances in accelerator neutrino physics is now widely recognized within the community, see e.g. documents prepared for the update of European Strategy for Particle Physics [1, 2].

The IN2P3 physicists have played a leading role in obtaining the NA61/SHINE results with both a thin carbon target [3] and a T2K replica target [4]. There measurements are currently being used to reduce the (anti)neutrino flux uncertainties in T2K and T2K-II down to about 5%.

Similar measurements are planned for the new target to be used for the HK experiment. Moreover, a preparatory work has now started to allow the NA61/SHINE spectrometer to be served with a lower-energy (below 10 GeV/c) beamline which is crucial for further reduction of uncertainties on both accelerator and atmospheric (anti-)neutrino fluxes in the HK era.

A.2 Constraints of flux and neutrino cross-section systematic uncertainties with INGRID and ND280

The biggest challenge for the Hyper-Kamiokande experiment will be the control of systematic uncertainties at the unprecedented level of about 2%. The most complex and large systematic uncertainties are due to flux and neutrino-nucleus cross-section, as shown, for instance, in Ref. [5]. The Hyper-Kamiokande strategy is based on the successfull experience of T2K, where the near detector (ND280) has a crucial role to constrain such systematic uncertainties. The French group had a primary role in the construction, maintenance and data exploitation of **INGRID**, **WAGASCI** and **ND280**(b.q). A first important role will be the continuation (? operation? BP) of the INGRID and WAGASCI detectors (during the HK data-taking? BP) coupled to the development of new analyses required to bring the HK systematic uncertainties down to their (required? BP) limits. Moreover, we have today a leading role in the upgrade of the ND280 detector currently in preparation of for the higher statistics expected after the J-PARC beam upgrade.

ND280 is a magnetized detector with outstanding tracking performances. It allows a precise measurement of the wrong sign background (measurement of neutrino background in the antineutrino beam and viceversa), which is compulsory for the discovery of leptonic CP-violation. The upgrade of ND280 includes a new concept of 3D finely-segmented scintillator detector (superFGD) capable of exclusive measurements of the hadronic final states in neutrino-nucleus interactions. The superFGD enables the reconstruction of the neutrino energy with a calorimetric approach, also in presence of neutrons, thus validating the neutrino energy reconstruction based only on muon kinematics which is a large source of systematic uncertainty in the Hyper-Kamiokande water Cherenkov detector.

ND280 is a modular detector which can be further upgraded, on the basis of the results obtained with larger statistics, in order to match the challenges which the Hyper-Kamiokande experiment will certainly face in the run to the ultimate precision in neutrino oscillation measurements.

A.3 Hyper-Kamiokande Far Detector

A.3.1 20-inch PMTs and their electronics

The photo-sensor for the inner detector of HK is newly developed. In the baseline option, around 20,000 20-inch PMT R12860-HQE are used. R12860-HQE PMTs have better timing and charge resolutions compared with the same diameter PMTs (R3600), which has been used in SK. The dark noise rate is required not to exceed 4 kHz, which is a similar requirement to the R3600 PMTs. Based on this information, the total data rate is estimated demonstrating that a DAQ system design similar to that of SK-IV is feasible.

The front-end electronics modules for the detectors are required to digitize all signals from photosensors above a certain threshold, i.e. the acquisition must be self-triggered. The digitized information is then either recorded or discarded, depending on the decision of the detector wide trigger system. If the front-end electronics modules is located on the top of the detector, it is necessary to run the cables from the PMT to the roof and the detector structure has to support their weight, which is expected to be about 800 tons. It would be possible to simplify the detector structure if we can reduce this weight. Also, the maximum length of the cable is $\sim 30\%$ longer than in the SK case. This not only reduces the signal amplitude, but also degrades the quality of the signal – the leading edge is smoothed out due to higher attenuation of the cable in the high frequency region. Therefore, we plan to place the modules with the front-end electronics and power supplies for the photo-sensors in the water, close to the photo-sensors.

The current baseline design of the front-end module takes all these requirements into account. There are 4 main function blocks in the front-end board: the signal digitization block, the photo-sensor power supply block, the slow control block and the communication block. In the current baseline design, one module accepts signals from 24 photo-sensors, digitizes them and sends out the data.

The signal digitization block accepts the signals from the photo-sensors and digitizes both the timing and the charge. One possible way to satisfy the requirements is to employ charge-to-time conversion (QTC) chips (b.q) which is currently used in the front-end module of SK-IV, called the QBEE. The QTC chip receives the signal from the photo-sensor and produces a digital signal, whose width is linearly dependent on the amount of the input charge.

We propose to develop and produce the Front-End electronics of HK, using an alternative to the QTC chip. This new chip is based on a new version of the current CATIROC chip developed by OMEGA laboratory, and used for the readout of JUNO 3" PMTs. This new chip is developed with several goals: extend its commercial availability compared to the QTC chip, reduce the deadtime and increase chip durability. The current QTC chip, as well as the current generation CATIROC, are printed in AMS 350 nm. This technology is closed to reach its expiration date, which will limit the time for R&D of QTC or current CATIROC, as well as conflict with a potential future production of this chip for a later upgrade of the detector. We propose to develop a new chip in TSMC 130 nm. On top of its longer availability, this technology allows to reduce the time required for readout, decrease the electronic noise as well as the cross-talk between the channels of the same chip. Moreover, the new flip chip packaging will be used for this chip, allowing to improve the chip durability. It is especially crucial for HK which will run several decades with the electronics in water. The new chip will also relies on an improved analog part compared to the CATIROC, allowing to reduce the conversion deadtime. Such an almost deadtime free chip would have significant improvement on HK physics, among which:

- increase the number of detected events for galactic Supernovae, and therefore improve the constraints on the explosion mechanisms.
- reduce the experiment energy threshold through monitoring of the so-called "continuous dark-rate".
- detect very prompt decay electrons, even produce few hunder nanosecond after the ini (??? BP)
- distinguish photons from direct and reflected light, therefore improving the energy reconstruction and ring counting especially at very high energies.

The OMEGA group will be responsible of the chip R&D. In parallel, the LLR group proposes to develop and produce the Front-End board hosting the chip. Not only the two laboratories are physically located on the same site, but they have also the experience of several successful collaborations in various projects, among which the T2K WAGASCI and Super-FGD or the CMS-HGCAL detectors.

The leading edge of the output digital signal corresponds to the time when the input signal exceeds a pre-defined threshold to produce the output digital signal. This output is read out by a TDC. The QTC chips (CLC101) used in the front-end module of SK-IV, called the QBEE, are a good reference and satisfy all the requirements. Even though the current baseline design is to use the QTC-TDC approach, the possibility of adopting Flash-ADC (FADC) type digitization is also investigated. In this case, the FADC chip would run all the time and digitize the input signal. Afterwards, FPGA-based on-the-fly digital signal processing would be utilized to find the PMT pulse and determine its charge and time of arrival. An advantage of this approach is that it is completely dead-time free – photons could be detected both from prompt muons and from decay electrons, even if this occurs only 100 ns after the initial interaction. We may also be able to distinguish photons from direct and reflected light. The disadvantage is potentially larger power consumption and higher cost.

A.3.2 Multi–PMTs option for HK

In addition to this baseline design, R&D on alternative photosensor options like hybrid photo-detectors, LAPPDs and multi-PMT (mPMT) modules is actively being carried on by several countries (mostly Canada, Italy, UK) with the goal of providing half of the photo–cathode coverage for Hyper-Kamiokande. The multi-PMTs are also the baseline photosensor option for the Intermediate Water Cherenkov Detector (IWCD). This option is particularly appealing for French groups as they could profit from the existing KM3NeT expertise and from the developments of the small PMTs for JUNO. In 2019 we plan to organize a workshop in order to exploit these possible synergies.

In addition there is the attractive possibility of using the existing Memphyno water tank [6] at APC for performing underwater tests of the mPMT modules developed in Europe, Canada and Japan and further characterize the in-situ response of the mPMTs. Such tests are expected to begin have already been started with the first mPMT prototype from Italy before summer 2019 and will be continued with a second prototype that is expected to be ready in the fall of 2019 and will continue in the coming years.

There is also a possibility of contributing to the development of electronics for the mPMTs readout based on a chip designed by the Omega laboratory.

In addition, a **test beam experiment** to be carried out at CERN with a tank instrumented with ~ 100 mPMTs is being proposed by a part of the Hyper-K collaboration. This design corresponds to a downscaled version of the Intermediate Water Cherenkov Detector (E61), proposed in the Hyper-K design to better control the cross-sections related uncertainties. This experiment aims at:

- test the technological choices for E61 and Hyper-K far detector in terms of modules synchronization, DAQ and storage;
- characterize the mPMTs response with respect to a calibrated source of charged particles, allowing to further constraint the simulations.

Our contribution to this test beam experiment will be a continuation of the work carried on the mPMTs studies (Proposal m.g.) and DAQ software development on with Memphyno. (Proposal m.g.) We intend to contribute to the data analysis and the extraction of the detectors performances.

The performances of a hybrid design for HK with a combination of large PMTs and multi-PMTs are being studies by the collaboration. Preliminary study results show that if the dark noise can be kept at the level of 100 Hz, better vertex reconstruction for events close to the wall and a lower energy threshold can be obtained. The better vertex reconstruction will allow to increase the Fiducial Volume while the lower energy threshold will improve performances for low energy events, in particular increasing the sensitivity of HK to the up-turn of the ⁸B spectrum of solar neutrinos, probing the MSW-LMA prediction in the transition region between vacuum and matter-dominated neutrino oscillations.

A.3.3 Clock distribution and time synchronization for small and large PMTs

Our possible contributions could be related to the communication block and in particular to the time synchronization and clock distribution for both the large PMTs and mPMTs since it represents a critical part of the experiment and we do have, in our electronic groups, experts on this kind of technology.

The main components of the communication block are timing synchronization, data handling and communication. TDCs or FADCs timing synchronization is crucial for precise measurements of photon arrival and, to achieve this goal, we are planning to distribute the common system clock and the reference counters to all the modules. In Hyper-Kamiokande, timing resolution of the photo-sensor is expected to be largely improved with respect to SK, at the level of 1 ns; therefore, we have to be careful with the synchronization of the modules and the clock jitter.

Clock distribution methods for Hyper-K, will be based on serial links with clock reconstruction. Many different options are under consideration, like SK and Belle-II schemes, as well as the CERN White Rabbit technology [7] or a possible custom solution. The implemented synchronization channel could be also used to perform sensitive slow control tasks as the FPGAs remote upload while mesh topology and multiple connections schemes will be developed in order to avoid single point failures. The chosen time synchronization system could be tested on a smaller scale on test beam at CERN and could also be used for the IWCD.

To our mind, an advantage of this task is that it is independent on the chosen technology for the PMTs and could be useful for both large and small PMTs assembled together in the mPMTs.

A.4 Software and Computing

The very performant IN2P3 Computing Centre (CC-IN2P3) at Lyon will allow us to play a leading role in the Hyper-K software and computing group.

(b.q, m.g) The French groups are already leading the development of new simulation and reconstruction tools for both low and high energy sectors. We plan to strenghten this contribution by:

- upgrading the simulation of the PMT front-end and clock-distribution systems in synergy with our progress on hardware,
- developing a new generation of reconstruction algorithms for Water Cherenkov detectors based on Machine Learning techniques,
- providing storage and computing resources from CC-IN2P3 to Hyper-K using DIRAC [8].

(Proposal m.g.) Several plans (? options? BP) to fund this last contribution are currently being discussed with CC-IN2P3 and IN2P3 directorate.

This will also allow us to exploit synergies with Belle-II groups in the context of the already-funded JENNIFER-II European project.

References

- [1] Andrea Dell'Acqua et al. "Future Opportunities in Accelerator-based Neutrino Physics". In: (2018). arXiv: 1812.06739.
- [2] Aysel Kayis Topaksu et al. "Research and Development for Near Detector Systems Towards Long Term Evolution of Ultra-precise Long-baseline Neutrino Experiments". In: (2019). arXiv: 1901. 04346.
- [3] N. Abgrall et al. "Measurements of π^{\pm} , K^{\pm} , K^{0}_{S} , Λ and proton production in proton-carbon interactions at 31 GeV/c with the NA61/SHINE spectrometer at the CERN SPS". In: *Eur. Phys. J. C* 76.2 (2015), p. 84. arXiv: 1510.02703.
- [4] N. Abgrall et al. "Measurements of π[±], K[±] and proton yields from the surface of the T2K replica target for incoming 31 GeV/c protons with the NA61/SHINE spectrometer at the CERN SPS". In: Eur. Phys. J. C 79.2 (2018), p. 100. arXiv: 1808.04927.
- [5] K. Abe et al. "Measurement of neutrino and antineutrino oscillations by the T2K experiment including a new additional sample of ν_e interactions at the far detector". In: *Phys. Rev.* D96.9 (2017), p. 092006. arXiv: 1707.01048.
- [6] Alessandra Tonazzo. "The LAGUNA-LBNO Project". In: Nucl. Part. Phys. Proc. 265-266 (2015), pp. 192–194.
- [7] Maciej Lipinski et al. "White rabbit: a PTP application for robust sub-nanosecond synchronization". In: (2011), pp. 25–30.
- [8] A Tsaregorodtsev et al. "DIRAC: a community grid solution". In: Journal of Physics: Conference Series 119.6 (2008), p. 062048.