


ProtoDUNE CRP status

09/07/2020


*B.Aimard, G.Deleglise, D.Duchesneau, N.Geffroy,
H.Meringolo, J-M.Nappa, F.Peltier, S.Vilalte*

Modal study to evaluate CRP stiffness based on first deformation mode (saddle shape)

Previous design



New design



	Initial	Optimised
Static / 100N : max displacement	27mm	0,1 mm
First eigenfrequency	2 Hz	15,6 Hz
Invar mass	140 kg	160 kg


Main beams

Reduced thickness : 6mm --> 4mm



Ansys mass/stiffness optimization - Lazer cut openings

Soles stiffeners

Th.=6mm





Previous design :




Upgraded design :

- Suppression of numerous parts
- No machining on the edges
- Globally simplified machining
- Strengthening of weak parts
- Prod. open to new manufacturers



50 suspensions points between invar and G10



New design

Widened and machined washers for better hole covering

--> easier planarity adjustment procedure


--> improved planarity of CRP under thermal contraction

Only one circlips

--> simplified solution for production and assembly

Self-locking thread inserts

-> brass to avoid stainless steel seizure




Previous design



Narrower PCBs : **40 wires** (prev. 64)
3,125mm step is preserved

Electrical protection : **Spark guides**



Excedent charge collection :
Resistive combs

Comb **each 50cm** (prev. each meter)






- Electrostatic force is higher than gravity during operation





- Electrostatic force is higher than gravity during operation

Combs **thickening to 0,5mm** (prev. 0,2mm)


- Better wire support
- Gap between LEMs is wider : 1 mm (prev. 0,5-0,8)
 - CRP dimension maintained, LEMs/Anodes dimensions are reduced








Resistive plated material (Kapton)
--> Plated both sides







Resistive plated material (Kapton)


--> Plated both sides

- Plating test to be done soon at CERN
- To be sized and validated by electrostatic simulations






➤ To be validated by electrostatic simulations




SparkGuide : Evaluation of the field perturbation

- Vertical direction
- Corner of the CRP
- Nominal fields :
 - Gas : 3300 V/cm
 - Liquid : 2260 V/cm


Material	Permittivity	Source
GAr	1.000513	From 3x1x1
LAr	1.505	MicroBoone
Copper	1000	High Value
Stainless Steel	1000	High Value
FR-4	3,5	Common value






Spark guide : Floating (similar to the existing CRP)

Criteria : Gas




Spark guide : Floating (similar to the existing CRP)

Criteria : Liquid




Spark guide : Ground

Criteria : Gas




Spark guide : Ground

Criteria : Liquid




Spark guide : -2,5kV

Criteria : Gas




Spark guide : -2,5kV

Criteria : Liquid




Spark guide : -3kV

Criteria : Gas



Spark guide : -3kV

Criteria : Liquid



Distance from PCB in mm for vertical electrical field variation of >10% or >20%

Spark
guide
voltage


Impact Gas	10%	20%
Floating	8,5	7,5
Ground	18	12,5
-2,5kV	12,5	9,5
-3kV	12,5	8


Impact Liquid	10%	20%
Floating	8	5
Ground	20	10
-2,5kV	12,5	9
-3kV	12	8

Parameters and conditions to apply for optimisation have to be agreed


- Hypothesis: All CRPs will be dismantled on place and evacuated without transport box
- CRP 1 & 2 replaced by 1bis and 2bis
- CRP 3 & 4 replaced by other type of detector
 - Study of technology compatibility and common run aspects

--> updated "Cabling layout" file available, to be finalized with cable lengths :






- Transport boxes from phase 1 will be reused, with minor modifications




- Minor changes in grid production tooling are necessary (support blocs machining)
- Storage system for grid subsets have to be designed for 2 - 3 full CRPs.



Mini-CRP : 1x1 meter facility to be used in ColdBox to validate :

- New LEM / Anodes design
- Instrumentation
- SparkGuides / Charge collection combs






G10 Support, Mini CRP
can be placed on a table




Windows
for camera

Removable combs




Transport box, to avoid dirts and damages

- External dimensions : 1438x1425x372 mm (to verify if compatible with B.182 elevator)
- Total weight with Mini-CRP : ~ 80 kg



Model is including :

- LEM/Anodes mass
- Gravity
- Cable suspensions
- Extraction grid mechanical tension (based on actual tension)
- Liquid temperature
- Thermal gradient in the gas ($2^{\circ}/\text{cm}$)




Displacement results : **0,1mm**

Vertical direction, max planarity defect

- Mostly caused by beams thermal deformation
- Initial planarity defect may be corrected by local wedging or weighting

Average stress in the structure : **20-60MPa**



Deformation due to grid tension is insignificant

