

# Accelerator and Beamline for Neutrino Long-Baseline Experiments

Megan Friend


KEK

May 25, 2023

## Outline

- How to make a neutrino beam for long-baseline neutrino experiments
- Accelerators for neutrino beamlines
- Neutrino beamline components
- Neutrino fluxes
- Errors on neutrino fluxes
  
- Using the J-PARC neutrino facility as an example
  - Neutrino source for current T2K and future Hyper-K experiments in Japan

# Producing A Neutrino Beam




- High energy protons from an accelerator hit a production target and produce hadrons
- Outgoing hadrons are sign selected + focused in electro-magnetic focusing horns
  - Change polarity of horn field to switch between focusing positive or negative hadrons
- Allow hadrons to decay in long decay volume:  $\pi^+ \rightarrow \mu^+ + \nu_\mu, \dots$
- Monitor hadrons in hadron monitor at downstream of decay volume, or muons in muon monitor installed in shielding/beam dump
- Stop protons, hadrons, muons, in beam dump or ground, while neutrinos continue on to near and far detectors

## Increasing the Neutrino Flux

- Neutrinos are very weakly interacting – want to increase the neutrino flux as much as possible
- How do we increase the number of neutrinos?  
→ First step is to increase the number of protons
- Two ways to increase the proton beam power:
  - ① Increase the frequency, number of beam spills
    - Increase beam repetition rate
    - (Maximize beam operation time..)
  - ② Increase the number of protons per spill
    - Reduce beam instabilities and beam losses
    - Of course, after increasing the proton beam power, all components in the neutrino extraction beamline must be able to handle the increased power
- – And – there are ways to increase the *effective* number of protons
  - i.e. improve the target to increase right-sign hadrons, increase/tune the horn current for better right-sign hadron focusing
- Also important to run the neutrino experiment as much as possible !

# High-Power Proton Source – J-PARC



- Accelerates proton beam to 30 GeV by:
  - 400 MeV Linac (linear accelerator) → 3 GeV RCS (Rapid Cycling Synchrotron) → 30 GeV MR (Main Ring Synchrotron)

## Ion Source

- Accelerator chain begins with an ion source
  - Radio-Frequency (RF) driven plasma discharge
- Produces  $H^-$  ions (proton with 2 electrons)
- Why use an  $H^-$  source, rather than proton ?
  - $H^-$  easier to handle at ion source
  - After acceleration in Linac, stripping charge to convert to protons allows for easy separation between particles (opposite forces in applied field)




Figure from <https://doi.org/10.1063/1.4995773>

# Radio-Frequency (RF) Cavities

- Radio-frequency cavities are the building block of any accelerator
  - High-frequency, high-power electromagnetic cavities
- Charged particles traveling through the cavity at the correct timing and energy are accelerated
  - By an electrical impulse from the field produced by the RF cavity



## Beam Transport

- Particle beams are transported through beam ducts
  - Beam ducts and accelerating cavities where the particles travel must be kept at high vacuum
    - To prevent collision of the particles accelerated inside the beam ducts with gas molecules in the beam pipe
  - Charged particles of the same charge sign repel each other (space-charge effects from the Coulomb force)
    - Must prevent beam size blow-up by focusing the particle beam
    - Use focusing magnets (quadrupole magnets) with some periodicity to focus the particle beam as it propagates



Figure from



# Linear Accelerator (LINAC)

- Accelerates 50keV  $H^-$  ions from the ion source to 400MeV by four stages of DC linear accelerators:
  - Radio Frequency Quadrupole Linac – 50keV → 3MeV
  - Drift Tube Linac – 3MeV → 50MeV
  - Separated-type Drift Tube Linac – 50MeV → 191MeV
  - Annular-ring Coupled Structure linac – 191MeV → 400MeV

Ion Source



RFQ outside



RFQ inside



DTL inside



Figures from

<https://j-parc.jp/c/facilities/accelerators/index.html>

## H<sup>-</sup> Stripping

- H<sup>-</sup> ions are stripped of two electrons (converted to protons) after acceleration in the linac, as they are being injected into the next accelerator (RCS)
  - This conversion means that the particles move opposite directions in the applied magnetic field
- Use a very thin charge-stripping foil (carbon)
  - More advanced techniques – laser stripping – under development
- At injection point (bunching), again need to worry about beam blow up by space-charge effects

- RCS injection point:
- Particles come from the linac (right) and enter the RCS (left)




## Rapid Cycling Synchrotron (RCS)

- In a linear accelerator, each particle only passes through each RF cavity a single time
- In a circular accelerator, the beam is recirculated  $>10,000$  times, passing each accelerating cavity each time
- In a Synchrotron, the fields which bend the particle around the fixed orbit increase “synchronized” with the increasing particle energy
- J-PARC RCS:
  - $\sim 350\text{m}$  circumference
  - Accelerates protons  $400\text{MeV} \rightarrow 3\text{GeV}$  in  $\sim 20\text{ms}$
  - Operation cycle of  $25\text{Hz}$ 
    - Injection, acceleration, extraction, field decrease happen in  $40\text{ms}$



<https://j-parc.jp/c/facilities/accelerators/index.html>

# Main Ring Synchrotron (MR)





- J-PARC Main Ring Synchrotron
- Accelerates protons  $3\text{GeV} \rightarrow 30\text{GeV}$
- 3-fold symmetric straight and bending sections
- 1568-m circumference
- 8-bunch beam structure

- 3 116-m-long straight sections dedicated to:
  - Injection and beam collimators
  - Slow extraction
  - Fast extraction and RF system  
→ Fast extraction to neutrino target

## Fast Extraction System

- Beam is extracted from the MR by kicker and septum magnets
  - Kicker magnet applies a time-dependent magnetic field
    - Fast, precise timing is necessary
  - Septum magnet applies a space-dependent magnetic field
    - Field localization is important – high field at extraction line must drop to 0 at recirculating line




New eddy current septum magnet

Low field septum magnets were replaced by eddy current magnets.


Leakage field was reduced

## Beam Dump

- The beam dump is another component that can limit the operation of the accelerator
- During MR beam study/tuning, or when the beam is aborted, the beam is kicked to a beam dump
- The current J-PARC MR beam dump is passively cooled iron blocks in concrete
  - Operational capacity of only  $\sim 18$  shots per hour at full beam power – significantly limits time which can be spent on accelerator tuning, especially as beam intensity is increased
- Now considering upgrades to increase capacity  $3\sim 4\times$



# Typical MR FX Operation




T. Yasui, NuFact2022

## MR Upgrade Operation

$$\text{Power} = \frac{\text{Energy} \times \text{Number of protons}}{\text{Cycle time}}$$

30 GeV


JFY2021	515 kW	$2.66 \times 10^{14}$ ppp	2.48 s
JFY2023	750 kW	$2.1 \times 10^{14}$ ppp	1.36 s
Future	1300 kW	$3.3 \times 10^{14}$ ppp	1.16 s





## Increasing the MR Proton Beam Power

- In 2020, J-PARC MR accelerator delivered  $\sim 2.65 \times 10^{14}$  protons every 2.48 seconds = 515 kW
- Now increasing the beam power in 2 ways:
  - Upgrade PSs + RF to reduce the time between beam spills from 1 spill every 2.48s  $\rightarrow$  1.36s  $\rightarrow$  1.16s
  - Improve stability to increase the number of protons per spill from  $\sim 2.65 \times 10^{14} \rightarrow 3.2 \times 10^{14}$       515 kW  $\rightarrow$  >700 kW  $\rightarrow$  1.3 MW



	Achieved	Target
Beam power [MW]	0.5	1.3
	$\sim 3\times$	
# of protons per pulse	$2.6 \times 10^{14}$	$3.2 \times 10^{14}$
	$+30\%$	
Rep. Time [sec]	2.48	1.16
	$\sim 1/2$	

# MR Upgrades Towards 1.3MW

JFY	2020	2021	2022	2023	2024	2025	2026	2027	2028
Event		Long Shutdown							
FX power [kW]	515	-	>700	800	900	>1000	>1100	>1200	1300
SX power [kW]	55	60-70	>80	>80	>80	>80	~100	~100	~100
Cycle time for Fast Extraction New Magnet PS	2.48s		1.32s	1.32s	1.32s	1.32s	<1.32s	<1.32s	1.16s
RF system upgrade			←————→						
2 <sup>nd</sup> RF system upgrade	————→								
Collimator system		Add.colli. (3.5kW)							
Injection system FX system	Kicker PS improvement Septa manufacture Test →								
Beam Monitors (BPM circuits)	————→								
SX: Diffuser/Bent crystal/VHF Local shield	←————→								


Prog. Theor. Exp. Phys. 2021, 033G01

# MR Power Supply Upgrade

- New MR magnet power supplies with energy recovery with capacitor banks developed
  - Allow for 1.36s repetition rate
- Installed in 2021
- Power supplies tested in-situ in April and May 2022
- Took first neutrino beam with 30GeV, 1.36s cycle repetition protons from the J-PARC MR in April 2023 → Achieved record 540kW!



# High-Power Proton Source – J-PARC




- Accelerates proton beam to 30 GeV by:
  - 400 MeV Linac (linear accelerator) → 3 GeV RCS (Rapid Cycling Synchrotron) → 30 GeV MR (Main Ring Synchrotron)

# High-Power Proton Source – Fermilab

## Fermilab Accelerator Complex




# J-PARC Neutrino Beamline



# J-PARC Neutrino Primary Beamline

**Final focusing (FF) section**  
10 normal conducting magnets




**Preparation section**  
11 normal conducting magnets

**Arc section**  
28 superconducting combined  
func. magnets



- Beam orbit (and beam loss) should be firmly controlled anytime.


# J-PARC Neutrino Primary Beamline



- Arc section : superconducting combined-function magnets
  - Used to sharply bend the beam towards the Super Kamiokande direction


- Preparation section : normal conducting dipole and quadrupole magnets
  - Used to bend and focus the proton beam extracted from the MR accelerator
  - Prepare the beam to be safely transported through the superconducting Arc section
- Final Focusing section : normal conducting dipole and quadrupole magnets
  - Used to bend and focus the proton beam correctly onto the neutrino production target
  - Proton beam position, angle, size at the target must be carefully controlled





## Beam Monitoring

Beam Direction →





### Beamline Final Focusing Section

- Beam monitors are essential for protecting beamline equipment and understanding proton beam parameters for flux simulation
- At J-PARC neutrino beamline, various monitors are installed along the beamline:
  - Current Transformers – monitor beam intensity
  - Beam Loss Monitors
  - Electrostatic Monitors – monitor beam position
  - Segmented/Wire Secondary Emission Monitors – non-continuously monitor beam profile
  - Optical Transition Radiation Monitor – continuously monitors beam at target
  - Muon Monitor – monitors tertiary muon beam profile


# Neutrino Secondary Beamline

- Neutrino production target and focusing horns for J-PARC neutrino beamline are kept in a gigantic He vessel
  - $\sim 1500 \text{ m}^3$  He vessel (world's largest?)
  - He-filled to minimize production of tritium and  $\text{NO}_x$  by interaction of high-energy hadrons with air



## Neutrino Production Target

- Goal for target – increase the number of proton interactions as much as possible to maximize the number of neutrinos produced
  - Another important part – Don't degrade ! Don't break !
- J-PARC neutrino production target consists of a long, monolithic carbon target
  - 91.4cm long (1.9 interaction length), cooled by He gas
- Other world-wide targets have different configurations (ie array of fins, different materials, water cooling, etc)



- R&D to establish new target types to further maximize number of produced neutrinos is ongoing
- Higher-density and/or hybrid materials, longer targets


## Neutrino Production Target Upgrade Ideas

- Longer term studies to establish new target types to further maximize number of produced neutrinos are also ongoing
  - Possible to increase pion yield and decrease forward-going (non-horn-focused) wrong-sign component by new target design
  - Higher-density and/or hybrid materials, longer targets

One example new target idea – insert 2nd (higher density?) target into downstream end of Horn 1:


### Current T2K target

90 cm graphite




### Changed target geometry

90 cm graphite + 65 cm 2<sup>nd</sup> target




## Electromagnetic Focusing Horns



- Electromagnetic focusing horn consists of inner and outer conductor
  - Large magnetic field between conductors achieved by flowing high current down one conductor and back along the other
    - Generally 100–300 kA – T2K used 250kA, now upgraded to 320kA
- Pions of the correct sign traveling between two conductors are focused
  - Sign of focused pions chosen based on direction of flowed current
- Generally cooled by water spray between 2 conductors
- J-PARC has 3 horn configuration (other beamlines in the world have 1~3 horns)
  - Horn 1 over-focuses some outgoing particles, Horns 2 and 3 correct path of focused and over-focused particles

## J-PARC Horns

- Horn 1 (bottom) and Horn 3 (right)
- Horns held in place from above by support modules mounted to ceiling of He vessel




## Decay Volume and Beam Dump

- Decay volume is just a big empty space where particles produced in the target can propagate and decay
- J-PARC neutrino beamline has 96m-long decay volume (similar at facilities around the world)
- J-PARC neutrino beamline decay volume is connected to He vessel – also He-filled to minimize production of tritium and NO<sub>x</sub> by interaction of high-energy hadrons with air
- Beam dump is graphite + iron blocks (~5m) to stop hadrons
- Water-cooled by coils



## Hadron/Muon Monitor

- Detect hadrons or muons after decay volume to understand hadron/muon (+ neutrino) beam direction, profile
  - Upstream (hadron monitor) or inside (muon monitor) of the beam dump
- Use large array of radiation-tolerant detectors to reconstruct the hadron/muon beam profile







## MUMON (Muon Monitor)

- Continuously monitors muon beam profile downstream of the decay volume, beam dump ( $> \sim 5$  GeV muons)
  - Ensure alignment, healthiness of target, horns; proton beam position, angle at target; etc
- 2 redundant measurements of the muon beam profile, position using  $7 \times 7$  arrays of sensors
  - Ionization chambers (IC) w/ Ar or He gas
  - Silicon photodiode sensors (Si)
- Same IC design used at Fermilab NUMI beamline
- Now developing upgraded sensors; Electron Multiplier Tube (EMT) under testing

## T2K Muon Monitors




## Controlling the Flux – Off-Axis Beam

Flux + Osc. Prob. at T2K

- “Off-axis” beam concept :
  - Due to pion decay kinematics, the neutrino energy depends on the outgoing neutrino angle:



$$E_\nu = \frac{(1 - (m_\mu/m_\pi)^2)E_\pi}{1 + \gamma^2\theta^2}$$

- So, an “off-axis” beam gives a smaller range of neutrino energies
- Many experiments use an off-axis beam to select a neutrino flux with a peak energy near the oscillation maximum
- Install detectors off-axis from the center of the neutrino beam to select the energy
- Precise understanding of the neutrino beam direction essential



# Flux Prediction



SK: Neutrino Mode,  $\nu_\mu$



- It is essential to not just produce a world-class neutrino beam, but also to understand the energy spectrum and number of produced neutrinos
- The  $\nu$  flux is predicted by simulations which take into account
  - Hadron interactions inside + outside the production target
  - Measured proton beam current, position, angle, profile
  - Measured neutrino beam angle
  - Measured Horn field, alignment
  - etc..

## Neutrino Parent Particles

- $\nu_\mu$  parent particle is mostly pions, which decay into  $\mu + \nu_\mu$  99.9% of the time
- However, kaons and other particles also contribute, especially at higher energies – produce some  $\nu_e$ 's, as well as muons
- Muons also decay, always produce  $\nu_\mu + \nu_e$
- Need to understand neutrino parent particles produced inside and outside of the target  
→ External hadron production experiments




	channel	BR [%]
$\pi$	$\rightarrow \mu \nu_\mu$	99.9
	$\rightarrow e \nu_e$	$10^{-4}$
K	$\rightarrow \mu \nu_\mu$	63.5
	$\rightarrow \pi^0 e \nu_e$	5.1
	$\rightarrow \pi^0 \mu \nu_\mu$	3.3
$K_L^0$	$\rightarrow \pi e \nu_e$	40.5
	$\rightarrow \pi \mu \nu_\mu$	27.0
$\mu$	$\rightarrow e \nu_e \nu_\mu$	100

## Neutrino Parent Interactions



Percentage of neutrino-mode T2K far detector flux from in-target or out-of-target interactions :

	in-target primary int.	other than the in-target primary int. (out of target int.)
$\nu_{\mu}$	63.2%	36.8% (12.4%)
$\bar{\nu}_{\mu}$	41.5%	58.5% (45.1%)
$\nu_e$	61.7%	38.3% (12.7%)
$\bar{\nu}_e$	54.0%	46.0% (27.2%)




- In-target primary interactions are the main contribution
- However, there is a significant contribution from secondary+tertiary and/or out of target interactions, especially for the wrong sign flux

# T2K Neutrino Fluxes




- Accelerators can produce a relatively pure beam of right-sign muon neutrinos (ie  $\nu_\mu$ 's in neutrino-mode and  $\bar{\nu}_\mu$ 's in antineutrino-mode)
- At J-PARC:
  - $\sim 3\%$  contamination of beam wrong-sign  $\nu_\mu$  at flux peak
  - $< 1\%$  contamination of beam  $\nu_e$  at flux peak

# Systematic Errors on the Neutrino Flux



- Total current flux errors are around  $\sim 5 \sim 10\%$  near the flux peak for various experiments
  - Can be (significantly) higher at low and high energies
- Significant contribution from **hadron production** uncertainties
- As hadron production errors are reduced by external measurements, errors related to **beamline hardware** are becoming important


# Hadron Production Errors on the Neutrino Flux



- Hadron production errors are coming from numerous relatively small sources – non-trivial to reduce (although we’re working on it!)
- Especially, interactions not constrained by external measurements – “Unconstrained interactions” – are becoming important
  - Try to constrain by additional data from dedicated hadron production measurements: NA61 @CERN, EMPHATIC @FNAL




# Hadron Production Errors on the Neutrino Flux



- These unconstrained and out-of-target secondary interactions are even more of an issue for the wrong-sign neutrino flux and beam intrinsic electron neutrino flux

# Non-Hadron Production Errors on the Neutrino Flux




- Non-hadron production errors (beamline hardware related errors) can also have  $\sim 5\%$  energy-dependent contribution
- Becoming more important as hadron production errors are reduced
- These errors are related to beamline hardware, so can be time-dependent – need to worry about correlations between different run periods, etc

## Conclusion

- Many components required to produce a high-intensity neutrino beam:
  - Proton source
  - Proton beam transport to the production target
  - Proper beam monitoring
  - Production target
  - Focusing horns
  - Decay volume/beam dump
  - Tertiary beam monitoring
- Essential to have a stable, high-intensity proton source
- Essential to have neutrino beamline components robust to beam heating, radiation damage, ...
- Essential to have a well-understood beamline in order to have a well-understood/well-constrained neutrino flux

## Backup Slides

# Neutrino Parent Particles



Neutrino parent particles are mostly **pions**, **kaons** produced in the target

$$\pi^\pm \rightarrow \mu^\pm + \nu_\mu(\bar{\nu}_\mu) \quad (\text{BR}=99.99\%) \quad (\text{right-sign low-E } \nu_\mu\text{'s})$$

$$K^\pm \rightarrow \mu^\pm + \nu_\mu(\bar{\nu}_\mu) \quad (\text{BR}=63.6\%) \quad (\text{right-sign high-E } \nu_\mu\text{'s})$$


$$\hookrightarrow \mu^\pm \rightarrow e^\pm + \bar{\nu}_\mu(\nu_\mu) + \nu_e(\bar{\nu}_e) \quad (\text{BR}=100\%) \quad (\text{right-sign } \nu_e\text{'s})$$

$$K_L \rightarrow \pi^\pm + \mu^\mp + \bar{\nu}_\mu(\nu_\mu) \quad (\text{BR}=27.0\%) \quad (\text{right- and wrong-sign } \nu_\mu\text{'s})$$

$$K_L \rightarrow \pi^\pm + e^\mp + \bar{\nu}_e(\nu_e) \quad (\text{BR}=40.6\%) \quad (\text{right- and wrong-sign } \nu_e\text{'s})$$

....

# Neutrino Parent Particles



Neutrino parent particles are mostly **pions** and **kaons** produced in the target, but can also be from particles produced by secondary interactions of **protons** and **neutrons** (+ **pions**, **kaons**, ...) in other materials around the beamline

$$\pi^\pm \rightarrow \mu^\pm + \nu_\mu(\bar{\nu}_\mu) \quad (\text{BR}=99.99\%) \quad (\text{right-sign low-E } \nu_\mu \text{'s})$$

$$K^\pm \rightarrow \mu^\pm + \nu_\mu(\bar{\nu}_\mu) \quad (\text{BR}=63.6\%) \quad (\text{right-sign high-E } \nu_\mu \text{'s})$$


$$\hookrightarrow \mu^\pm \rightarrow e^\pm + \bar{\nu}_\mu(\nu_\mu) + \nu_e(\bar{\nu}_e) \quad (\text{BR}=100\%) \quad (\text{right-sign } \nu_e \text{'s})$$

$$K_L \rightarrow \pi^\pm + \mu^\mp + \bar{\nu}_\mu(\nu_\mu) \quad (\text{BR}=27.0\%) \quad (\text{right- and wrong-sign } \nu_\mu \text{'s})$$

$$K_L \rightarrow \pi^\pm + e^\mp + \bar{\nu}_e(\nu_e) \quad (\text{BR}=40.6\%) \quad (\text{right- and wrong-sign } \nu_e \text{'s})$$


....

# Neutrino Parent Particles



- Main contribution of right-sign flux from right-sign pions near flux peak, right-sign kaons at higher energies
- Then hadrons produced by proton interactions with materials outside of the target, then others..


# Neutrino Parent Particles



- Main contribution of wrong-sign flux from wrong-sign pions, muons from right-sign pion decay
- Then hadrons produced by proton/neutron interactions with materials outside of the target




# Neutrino Parent Particles



- Main contribution of  $\nu_e$  flux from muon decay from right-sign pions and kaons
- Then  $K^0$ , hadrons produced by proton/neutron interactions with materials outside of the target, ...

# Neutrino Parent Particles





- Main contribution of  $\bar{\nu}_e$  flux from  $K_L^0$ , then muon decay from wrong-sign kaons
- Then hadrons produced by proton/neutron interactions with materials outside of the target, muon decay from wrong-sign pions, ...

# Beam Monitoring

# Beam Intensity Monitoring

## Current Transformer Concept




- A proton beam with current  $I_{beam}$  generates a magnetic field,  $\mathbf{B}$ , as it travels
  - Exactly like a wire carrying a current
- The magnetic field is felt by a transformer core around the beamline



- Magnetic field in core induces a secondary current,  $I_{sec}$  on a wire coiled around the core
- The beam acts as primary winding with  $N_{beam} = 1$ , so :
  - $I_{beam}/I_{sec} = N_{torus}/N_{beam} \rightarrow I_{sec} = I_{beam}/N_{torus}$
- Can measure beam current by adding a resistor and using Ohm's Law :  $V = R \times I_{sec} \rightarrow I_{sec} = V/R$
- So :  $I_{beam} = N_{torus} \times V/R$

## Current Transformer Concept


- When the proton beam travels along the beamline, a  $\sim$ equal but opposite “image charge” is induced on the (conducting) beampipe
- This image charge basically cancels the beam current, making monitoring through the beam pipe impossible !
- Must put a non-conducting “break” in the beamline to see the beam
  - High-frequency component of the image charge goes through series of resistors over the gap (so, not seen by the CT)
  - Conducting shell around the CT should allow the low-frequency component of the image charge to pass



## T2K Current Transformers


5 CTs (Current Transformers) + 2 R&D PPS-CTs

- Monitor proton beam intensity
- Cylindrical ferromagnetic core made of FINEMET<sup>®</sup> (nanocrystalline Fe-based soft magnetic material) from Hitachi Metals
- 50-turn toroidal coil
- Stainless steel + iron outer casing



## Signal From Current Transformers

- CT is read out/digitized by 160MHz ADC
  - Integrate total charge seen by CT, then convert to # of protons (1 proton =  $1.602 \times 10^{-19}$  C)
  - Very clearly see the time structure of the J-PARC proton beam






# Beam Loss Monitor

## Beam Loss Monitor

- Wire proportional counter filled with a mixture of  $\sim 90\%$  inert gas +  $\sim 10\%$  quench gas
- Ionizing particle produced by beam loss travels through the chamber, ionizes inert gas in the chamber, produces  $e^- - \text{ion}^+$  pairs
  - Number of pairs proportional to the energy of the particle
- An electric field in the chamber causes positive ions to drift towards the cathode and electrons towards the anode
- Near the anode wire, the field strength is large enough to produce an avalanche to multiply the electron signal for readout
  - Should only produce one avalanche per electron-ion pair for linear response



## T2K Beam Loss Monitors

### 50 BLMs (Beam Loss Monitors)

- Continuously monitor beam loss
- Wire proportional counter filled with an Ar-CO<sub>2</sub> mixture
- Ionizing particles produced by beam loss ionize gas in chamber  
~proportional to amount of beam loss
  - Actually, some BLM response function needed..
  - Down to very low levels of loss
- The BLM signal is integrated during each beam spill, and if it exceeds a set threshold a beam abort interlock signal is fired
- R&D for new BLM types (optical fiber, etc) is also underway at T2K




→ Extremely important for protecting beamline equipment and understanding residual radiation of beamline components

# Beam Position Monitoring

## Beam Position Monitor


- Standard beam position monitor uses 4 segmented cylindrical electrodes surrounding the proton beam orbit
  - Beam passage induces charge on electrodes proportional to distance from that electrode
- Asymmetry between signal from opposite electrodes gives beam position inside the beampipe :
  - $\frac{C_R - C_L}{C_R + C_L}$  gives beam X position
  - $\frac{C_U - C_D}{C_U + C_D}$  gives beam Y position



# T2K Beam Position Monitors

21 ESMs (Electrostatic Monitor) used in T2K extraction beamline

- Non-destructively, continuously monitor the proton beam position
  - Uses 4 simple, curved electrodes
  - Can be non-linearities, second order effects, especially away from monitor center
  - Can be effect due to scattered particles from other beam monitors
    - Improved designs, beyond simple 4-electrode one, also in use at different facilities




# Beam Profile Monitoring

- Beam profile = beam position + beam width

# Optical Transition Radiation Monitor (OTR)

- Optical Transition Radiation is produced when a charged particle travels between two materials with different dielectric constants
  - Light profile is proportional to charged particle beam profile
- If the material (foil) is placed at  $45^\circ$  with respect to the beam, can measure backwards-going OTR light at  $90^\circ$  from the beam direction






# T2K Optical Transition Radiation Monitor

## 1 OTR (Optical Transition Radiation Monitor)


- Continuously monitors beam profile directly upstream of the target
- Rotatable disk with 8 foil positions allows for many OTR target types
  - 50- $\mu\text{m}$ -thick Ti foil designed for standard data-taking
  - Ceramic foil (which produces fluorescent light) used for very low intensity beam
  - Ti foils with holes used for optical system calibration by back-lighting



# T2K Optical Transition Radiation Monitor


## 1 OTR (Optical Transition Radiation Monitor)

- Continuously monitors beam profile directly upstream of the target
- T2K OTR monitors backwards-going light from foil
  - Light is directed to TS ground floor by a series of 4 mirrors and then monitored by a radiation-hard camera



# Secondary Emission Monitor


## Secondary Emission Profile Monitor Principle



- Protons interact with foils inserted into the beam
- Secondary electrons are emitted from segmented cathode plane and collected on anode planes
  - Proportional to proton beam profile
- Compensating charge in each cathode strip is read out as positive polarity signal

## T2K Secondary Emission Monitor

T2K Profile Monitor : Segmented Secondary Emission Monitor (SSEM)



- Same principle, but single anode plane between two strippped cathode planes used to collect electrons
  - 1 strippped plane for X, 1 for Y
- 5  $\mu\text{m}$  thick Ti foils

## T2K SSEM<sub>s</sub>

### 19 SSEM<sub>s</sub> (Segmented Secondary Emission Monitor)

- Measure beam profile during tuning
  - 1 SSEM causes 0.005% beam loss  
→ Only most downstream SSEM (SSEM19) can be used continuously
- Two 5- $\mu\text{m}$ -thick titanium foils stripped horizontally and vertically, with a 5- $\mu\text{m}$ -thick anode HV foil between them
  - Strip width ranges from 2 to 5 mm, optimized according to the expected beam size
  - Remotely move into and out of the beamline
- SSEM19 is used for beam interlock – if beam profile at the target is outside of the allowed range, beam abort interlock signal is fired




# T2K Proton Beam Profile Monitor R&D

## Why Is Non-Destructive (+ Minimally-Destructive) Proton Beam Monitoring Important?

- Standard monitors measure the beam profile by intercepting the beam – they are *destructive* and cause *beam loss*
  - Absolute amount of beam loss is proportional to beam power and volume of material in the beam
- Beam loss can cause :
  - Irradiation of and damage to beamline equipment
  - Increased residual radiation levels in the beamline tunnel
- Foils in the beam may degrade
  - Rate of degradation will increase as the beam power increases
- The beam profile must be monitored continuously
  - So, R&D for J-PARC proton beam profile monitors that work well at high beam power is ongoing
    - Goal : reduce or eliminate beam loss due to profile monitor
    - Goal : work well for a long time, even at high beam power


# Measured Beam Loss Due to SSEMs



- Beam loss when SSEMs are IN is quite high
  - $\sim 0.005\%$  beam loss at each SSEM
- Can cause radiation damage, activation of beamline equipment
  - SSEMs upstream of the neutrino target station cannot be used continuously





## Observed Degradation



## WSEM Beam Profile Monitor

- Wire Secondary Emission Monitor (WSEM) designed to measure proton beam profile in the T2K beamline (same design used at Fermilab)
- Monitor beam profile using twinned 25  $\mu\text{m}$  Ti wires
  - Exact same principle as SSEMs but with reduced material in the beam  $\rightarrow$  beam loss reduced by factor of 1/10
  - C-shape allows monitor to be moved into and out of the beam while the beam is running
    - Wires mounted at  $45^\circ$  so they can measure X and Y



# Beam Induced Fluorescence Monitor (BIF)

- Protons hit gas (i.e.  $N_2$ , Xe) inside the beam pipe
- Gas molecules are excited by the interaction with the protons
  - Electrons in the gas promoted to excited (rotational, vibrational, etc) states
  - Gas may or may not be ionized (electrons ripped off)
- When electrons fall to a lower energy orbit, photons are emitted
  - Fluorescence of the gas
- Pattern of fluorescence light should be proportional to the proton beam profile that excited the gas

The states and transitions of  $N_2$  and  $N_2^+$  that have been observed in various modifications of active nitrogen are illustrated in Fig. 1. The Roman numerals tabulate the systems in the order of increasing electronic energy of the emitting state. The Arabic numerals represent the highest vibrational






FIG. 1. States and transitions of  $N_2$  and  $N_2^+$  that have been observed in various modifications of active nitrogen. (I) The Vegard-Kaplan (forbidden) bands,  $A^1\Sigma_g^+ \rightarrow X^1\Sigma_g^+$ . (II) The first positive system of  $N_2$ ,  $B^3\Pi_g \rightarrow A^1\Sigma_g^+$ . (III) The "Y" bands.




## Beam Induced Fluorescence Monitor Merit

- Measure beam profile by fluorescence induced by proton beam interactions with gas in the beamline
  - Need  $\sim 1000\text{km}$  of gas @  $1 \times 10^{-3}$  Pa to equal beam loss from 1 SSEM
    - Basically totally non-destructive (in T2K extraction line)
- Can be used to continuously and non-destructively monitor proton beam profile even at very high beam power !



# T2K Beam Induced Fluorescence Monitor

- Installed various components for full prototype monitor in neutrino primary beamline in 2019
  - Pulsed gas injection system
  - 2 systems for optical focusing, transport, light detection (1 horizontal, 1 vertical)



## Working Prototype BIF Monitor @T2K (!)

- Injected  $N_2$  gas into J-PARC neutrino primary beamline at the same timing as the proton beam
- Installed 2 different sensor arrays to observe produced BIF light from proton interactions with injected gas
- Made first observation of BIF light at J-PARC neutrino beamline last January (!)

