

# Super-FGD: an innovative scintillating target for near detectors

Jaafar Chakrani

*On behalf of the T2K collaboration*

Laboratoire Leprince-Ringuet (LLR)

<jaafar.chakrani@polytechnique.edu>

BSM-Nu third workshop


IJCLab, Orsay, France

May 25<sup>th</sup>, 2022




- **Introduction**
- **T2K Near Detector Upgrade**
- **Super-FGD construction**
- **Super-FGD prototypes**
- **Expected physics performances**
- **Summary and prospects**

# Introduction



- Main goals:
  - Measure  $\nu_e/\bar{\nu}_e$  appearance: sensitive to  $(\delta_{CP}, \theta_{13})$
  - Measure  $\nu_\mu/\bar{\nu}_\mu$  disappearance: sensitive to  $(\theta_{23}, \Delta m^2)$
- How?
  - Produce an intense  $\nu_\mu$  (or  $\bar{\nu}_\mu$ ) beam
  - Measure the unoscillated flux at the near detector complex to monitor the beam and constrain systematic uncertainties
  - Measure the oscillated flux at Super-Kamiokande





$$N_{\nu_\alpha}^{ND}(E_\nu) = \Phi_{\nu_\alpha}^{ND}(E_\nu) \times \epsilon^{ND}(E_\nu) \times \sigma_{\nu_\alpha}^{ND}(E_\nu)$$






$$N_{\nu_\beta}^{FD}(E_\nu) = \Phi_{\nu_\beta}^{FD}(E_\nu) \times \epsilon^{FD}(E_\nu) \times \sigma_{\nu_\beta}^{FD}(E_\nu) \times P_{\nu_\alpha \rightarrow \nu_\beta}(E_\nu)$$

Flux model
Detector model
Neutrino interaction model
Oscillation model

- Far/Near ratio does not fully cancel systematic uncertainties, e.g.:
  - ◆ Flux model different at ND vs. FD due to geometry and oscillation
  - ◆ Different detectors, *i.e.* different acceptance and efficiencies
  - ◆ Mainly  $\nu_\mu(\bar{\nu}_\mu)$  at ND interacting with CH  $\rightarrow$  use model to infer interactions of  $\nu_\mu/\nu_e(\bar{\nu}_\mu/\bar{\nu}_e)$  in  $\text{H}_2\text{O}$

$\rightarrow$  T2K's approach is to propagate the constraints on the **flux** and the **neutrino interaction** models from the ND to the FD

# Off-axis Near Detector at 280m (ND280)







Deep Inelastic Scattering event display

# Off-axis Near Detector at 280m (ND280)


Fine Grained Detectors (FGDs):

- Plastic scintillator tracker
- Target for neutrino interactions
- FGD2 has water target layers





Deep Inelastic Scattering event display

# Off-axis Near Detector at 280m (ND280)



## Time Projection Chambers (TPCs)




- Tracking detectors
- Charged particle momentum
- Particle ID



Deep Inelastic Scattering event display

# Off-axis Near Detector at 280m (ND280)


UA1 Magnet:  
• 0.2 T magnetic field for charge identification



Deep Inelastic Scattering event display

## T2K Oscillation Analysis strategy

5




$$N_{\nu_\alpha}^{ND}(E_\nu) = \Phi_{\nu_\alpha}^{ND}(E_\nu) \times \epsilon^{ND}(E_\nu) \times \sigma_{\nu_\alpha}^{ND}(E_\nu)$$

$$N_{\nu_\beta}^{FD}(E_\nu) = \Phi_{\nu_\beta}^{FD}(E_\nu) \times \epsilon^{FD}(E_\nu) \times \sigma_{\nu_\beta}^{FD}(E_\nu) \times P_{\nu_\alpha \rightarrow \nu_\beta}(E_\nu)$$

- Far/Near ratio does not fully cancel systematic uncertainties, e.g.:
  - Flux model different at ND vs. FD due to geometry and oscillation
  - Different detectors, i.e. different acceptance, efficiencies, targets...
  - Mainly  $\nu_\mu(\bar{\nu}_\mu)$  at ND interacting with CH  $\rightarrow$  use model to infer interactions of  $\nu_\mu/\nu_e(\bar{\nu}_\mu/\bar{\nu}_e)$  on  $H_2O$
- T2K's strategy is to propagate the constraints on the flux and the neutrino interaction models from the ND to the FD

Jaafar Chakrani (LLR)

NOW 2022 - Sep 6th, 2022




Scattering event display


ND280 has been able to provide quality measurements for T2K results, but with the **increasing statistics** its limitations on the **flux** and the **neutrino interaction model uncertainties** are starting to arise in the analyses

# Limitations of current ND280


- Non-isotropic efficiency (unlike Super-Kamiokande)
- High momentum proton threshold ( $\sim 450$  MeV/c)
- For the oscillation analysis, neutrino interactions are characterized in **muon kinematics only**




Muon neutrino events at ND280



Electron neutrino events at Super-K



Proton detection efficiency



⇒ T2K is currently upgrading ND280 to overcome these limitations





# T2K Near Detector Upgrade





# T2K ND280 Upgrade Overview


13


- Super-FGD:  $2 \cdot 10^6$   $1 \text{ cm}^3$  scintillator cubes
- New high-angle TPCs
- New Time Of Flight detector


**The goal is to reduce the ND systematics with:**

- Fully active target
- $4\pi$  acceptance for charged particles
- Lower proton momentum threshold ( $\sim 300 \text{ MeV}/c$ )
- Neutron kinematics reconstruction
- Larger statistics















# Super-FGD construction



- ~2 million 1x1x1 cm<sup>3</sup> cubes made of plastic scintillator → ~2 tons
- Cubes covered by reflector will be read out with 3 orthogonal WLS fibres each with MPPC on one end → total of 56,382 fibers



vs.




# Cube production and pre-assembly

- The production of the 2 million cubes was done by Uniplast (Vladimir, Russia), with a rate of **~100,000 cubes/month**, and took over 1.5 years




Compound of polystyrene + paraterphenyl loaded in this tank




~500 cubes/hour



Cubes delivered and Layers assembled VS Time




- The production of the 2 million cubes was done by Uniplast (Vladimir, Russia), with a rate of **~100,000 cubes/month**, and took over 1.5 years
- As the cubes were delivered, they were assembled **layer by layer** using fishing lines after quality checks






- The production of the 2 million cubes was done by Uniplast (Vladimir, Russia), with a rate of **~100,000 cubes/month**, and took over 1.5 years
- As the cubes were delivered, they were assembled **layer by layer** using fishing lines after quality checks


<https://www.wikihow.com/Make-a-Beaded-Bracelet>





- The production of the 2 million cubes was done by Uniplast (Vladimir, Russia), with a rate of **~100,000 cubes/month**, and took over 1.5 years
- As the cubes were delivered, they were assembled **layer by layer** using fishing lines after quality checks



Cubes delivered and Layers assembled VS Time



- The production of the 2 million cubes was done by Uniplast (Vladimir, Russia) with a rate of **~100,000 cubes/month**, and took



- The production of the 2 million cubes was done by Uniplast (Vladimir, Russia), with a rate of **~100,000 cubes/month**, and took over 1.5 years
- As the cubes were delivered, they were assembled **layer by layer** using fishing lines after quality checks
- The pre-assembled layers were shipped in two boxes to J-PARC by plane




The (empty) wooden shipment box weighs 500 kg

July 2022 at J-PARC





- The production of the 2 million cubes was done by Uniplast (Vladimir, Russia), with a rate of **~100,000 cubes/month**, and took over 1.5 years
- As the cubes were delivered, they were assembled **layer by layer** using fishing lines after quality checks
- The pre-assembled layers were shipped in two boxes to J-PARC by plane
- In the meantime, the Super-FGD box was being designed



1. Insert the 2 million cubes in the Super-FGD box layer by layer



1. Insert the 2 million cubes in the Super-FGD box layer by layer

Super-FGD box




1. Insert the 2 million cubes in the Super-FGD box layer by layer






1. Insert the 2 million cubes in the Super-FGD box layer by layer
2. Insert the fishing lines in the corresponding holes of the Super-FGD box for each layer




One SiPM  
per hole

1. Insert the 2 million cubes in the Super-FGD box layer by layer
2. Insert the fishing lines in the corresponding holes of the Super-FGD box for each layer
3. Ensure vertical alignment with vertical metal “rods” for each added layer



1. Insert the 2 million cubes in the Super-FGD box layer by layer
2. Insert the fishing lines in the corresponding holes of the Super-FGD box for each layer
3. Ensure vertical alignment with vertical metal “rods” for each added layer
4. Close the Super-FGD box











1. Insert the 2 million cubes in the Super-FGD box layer by layer
2. Insert the fishing lines in the corresponding holes of the Super-FGD box for each layer
3. Ensure vertical alignment with vertical metal “rods” for each added layer
4. Close the Super-FGD box
5. Replace the fishing lines with wavelength shifting (WLS) fibers



1. Insert the 2 million cubes in the Super-FGD box layer by layer
2. Insert the fishing lines in the corresponding holes of the Super-FGD box for each layer
3. Ensure vertical alignment with vertical metal “rods” for each added layer
4. Close the Super-FGD box
5. Replace the fishing lines with wavelength shifting (WLS) fibers
6. Check the light yield in each fiber





1. Insert the 2 million cubes in the Super-FGD box layer by layer
2. Insert the fishing lines in the corresponding holes of the Super-FGD box for each layer
3. Ensure vertical alignment with vertical metal “rods” for each added layer
4. Close the Super-FGD box
5. Replace the fishing lines with wavelength shifting (WLS) fibers
6. Check the light yield in each fiber
7. Attach SiPM boards on the sides of the box: one SiPM/fiber




MPPC64 board

1. Insert the 2 million cubes in the Super-FGD box layer by layer
2. Insert the fishing lines in the corresponding holes of the Super-FGD box for each layer
3. Ensure vertical alignment with vertical metal “rods” for each added layer
4. Close the Super-FGD box
5. Replace the fishing lines with wavelength shifting (WLS) fibers
6. Check the light yield in each fiber
7. Attach SiPM boards on the sides of the box: one SiPM/fiber
8. Install LED calibration system






1. Insert the 2 million cubes in the Super-FGD box layer by layer
2. Insert the fishing lines in the corresponding holes of the Super-FGD box for each layer
3. Ensure vertical alignment with vertical metal “rods” for each added layer
4. Close the Super-FGD box
5. Replace the fishing lines with wavelength shifting (WLS) fibers
6. Check the light yield in each fiber
7. Attach SiPM boards on the sides of the box: one SiPM/fiber
8. Install LED calibration system
9. Install light barriers






1. Insert the 2 million cubes in the Super-FGD box layer by layer
2. Insert the fishing lines in the corresponding holes of the Super-FGD box for each layer
3. Ensure vertical alignment with vertical metal “rods” for each added layer
4. Close the Super-FGD box
5. Replace the fishing lines with wavelength shifting (WLS) fibers
6. Check the light yield in each fiber
7. Attach SiPM boards on the sides of the Super-FGD box
8. Install LED calibration system
9. Install light barriers
10. Attach cables on the MPPC64 boards




1. Insert the 2 million cubes in the Super-FGD box layer by layer
2. Insert the fishing lines in the corresponding holes of the Super-FGD box for each layer
3. Ensure vertical alignment with vertical metal
4. Close the Super-FGD box
5. Replace the fishing lines with wavelength sh
6. Check the light yield in each fiber
7. Attach SiPM boards on the sides of the box
8. Install LED calibration system
9. Install light barriers
10. Attach cables on the MPPC64 boards
11. Install readout electronics (ongoing...)



- Total channels to read: **~56,000 channels** (i.e. SiPMs)
- A complex architecture of electronics is used for the readout:




- Total channels to read: **~56,000 channels** (i.e. SiPMs)
- A complex architecture of electronics is used for the readout:
  - ~220 front-end boards (FEBs), each reads up to 256 channels (using 8xCITIROC)





# Super-FGD readout electronics



- Total channels to read: **~56,000 channels** (i.e. SiPMs)
- A complex architecture of electronics is used for the readout:
  - ~220 front-end boards (FEBs), each reads up to 256 channels (using 8xCITIROC)
  - Arranged in 16 crates of 14 FEBs






# Super-FGD readout electronics


- Total channels to read: **~56,000 channels** (i.e. SiPMs)
- A complex architecture of electronics is used for the readout:
  - ~220 front-end boards (FEBs), each reads up to 256 channels (using 8xCITIROC)
  - Arranged in 16 crates of 14 FEBs
  - A series of intermediate boards allow to distribute the power, send the beam trigger, configure the FEBs, preprocess data, ...






- Total channels to read: **~56,000 channels** (i.e. SiPMs)
- A complex architecture of electronics is used for the readout:
  - ~220 front-end boards (FEBs), each reads up to 256 channels (using 8xCITIROC)
  - Arranged in 16 crates of 14 FEBs
  - A series of intermediate boards allow to distribute the power, send the beam trigger, configure the FEBs, preprocess data, ...
- Before launching the production of the FEBs, various performance tests were performed on prototypes to validate the final design




- Charge readout in all the 256 channels and basic calibration (pedestal, gains, etc.)




Amplitude calibration



- Charge readout in all the 256 channels and basic calibration (pedestal, gains, etc.)
- Channel-to-channel electronic cross talk




- Charge readout in all the 256 channels and basic calibration (pedestal, gains, etc.)
- Channel-to-channel electronic cross talk
- Channel-to-channel timing differences (will be calibrated in the actual Super-FGD setup)





- Charge readout in all the 256 channels and basic calibration (pedestal, gains, etc.)
- Channel-to-channel electronic cross talk
- Channel-to-channel timing differences (will be calibrated in the actual Super-FGD setup)
- Linearity of the FEB response




# FEB tests


- Charge readout in all the 256 channels and base
- Channel-to-channel electronic cross talk
- Channel-to-channel timing differences (will be setup)
- Linearity of the FEB response
- Impact of the 0.2-T magnetic field in the orient



CH 80



Channel 32




- Charge readout in all the 256 channels and basic calibration (pedestal, gains, etc.)
- Channel-to-channel electronic cross talk
- Channel-to-channel timing differences (will be calibrated in the actual Super-FGD setup)
- Linearity of the FEB response
- Impact of the 0.2-T magnetic field in the orientations expected in the Super-FGD setup
- Satisfactory performances with minimal changes to the design  
⇒ **Green light for mass production**
- Installation expected during this summer




# Prototypes of the Super-FGD

- Multiple beam tests with prototypes have been performed to confirm the Super-FGD concept:







Super-FGD prototype (8x24x48 cm)




US-Japan prototype (8x8x32 cm)



- Multiple beam tests with prototypes have been performed to confirm the Super-FGD concept:
  - At CERN with charged particles: [NIMA 936 \(2018\)](#), [JINST 15. 12 \(2020\)](#)




Super-FGD prototype (8x24x48 cm)




US-Japan prototype (8x8x32 cm)

- Multiple beam tests with prototypes have been performed to confirm the Super-FGD concept:
  - At CERN with charged particles: [NIMA 936 \(2018\)](#), [JINST 15. 12 \(2020\)](#)




Super-FGD prototype (8x24x48 cm)



Bragg peak from a stopping proton



dE/dx measured for different particles




Electron-gamma separation




US-Japan prototype (8x8x32 cm)

- At LANL with neutrons: [arxiv:2207.02685](#)
  - Measurement of the total cross section as a function of the neutron kinetic energy using event rate depletion along the beam axis:  $N(z) = N_0 e^{-T\sigma_{tot}z}$

Neutron Cross Section vs Neutron Energy




- Multiple beam tests with prototypes have been performed to confirm the Super-FGD concept:
  - At CERN with charged particles: [NIMA 936 \(2018\)](#), [JINST 15. 12 \(2020\)](#)




Super-FGD prototype (8x24x48 cm)



Bragg peak from a stopping proton



dE/dx measured for different particles



Electron-gamma separation




US-Japan prototype (8x8x32 cm)

- At LANL with neutrons: [arxiv:2207.02685](#)
  - Measurement of the total cross section as a function of the neutron kinetic energy using event rate depletion along the beam axis:

$$N(z) = N_0 e^{-T\sigma_{tot}z}$$

⇒ The tests show that the Super-FGD concept is promising!

Neutron Cross Section vs Neutron Energy







# Expected physics performances




# Expected performances

- Improved reconstruction at high and backward angles  
→ better constraints on the neutrino interaction model



Muon neutrinos at ND280




Electron neutrinos at Super-K





# Expected performances


- Improved reconstruction at high and backward angles  
→ better constraints on the neutrino interaction model
- Better reconstruction of outgoing nucleons  
→ access to new observables





# Expected performances

- Improved reconstruction at high and backward angles  
→ better constraints on the neutrino interaction model
- Better reconstruction of outgoing nucleons  
→ access to new observables

**Neutron kinematics reconstruction by measuring their time-of-flight when they interact within the Super-FGD**








Phys. Rev. D 101, 092003






# Expected performances

- Improved reconstruction at high and backward angles  
→ better constraints on the neutrino interaction model
- Better reconstruction of outgoing nucleons  
→ access to new observables
- Increased target mass (x2 current ND280)  
→ more statistics



# Expected performances

- Improved reconstruction at high and backward angles  
→ better constraints on the neutrino interaction model
  - Better reconstruction of outgoing nucleons  
→ access to new observables
  - Increased target mass (x2 current ND280)  
→ more statistics
- **Probe neutrino interaction physics at an unprecedented level!**





# Summary and prospects



- The Super-FGD is a new addition to the T2K near-detector complex as part of the ND280 upgrade
- It is a novel **highly granular** plastic scintillator tracker with a (quasi-)3D readout
- The Super-FGD is **fully assembled** and the installation of the electronics is expected early this Summer, with a full **commissioning before the Fall**
- The granularity of the Super-FGD is a key characteristic that allows it to precisely measure the kinematics of the outgoing particles from neutrino interactions, and particularly **hadrons with an unprecedented precision**