


# First ultracold neutrons for TUCAN

Alexis Brossard
On behalf of the TUCAN collaboration


Monday, September 22, 2025 Caen



# Step 1: Kicking (high energy) neutrons out of nucleus.




**Step 2: Moderation by elastic scattering.** 







## **Step 3: Superthermal conversion to UCNs**


Neutrons with  $E \approx 1$  meV can transfer their energy to an excitation of the scattering medium, a phonon.







## Step 1: Kicking (high energy) neutrons out of nucleus







**Tantalum-clad tungsten target** 





Temperature profile at the center of the target.


## **Step 2: Moderation by elastic scattering.**

#### The moderation is made in:

- 546 L of room temperature heavy water
- 125 L of 20 K liquid deuterium











Cold neutrons are converted to UCN in isopure <sup>4</sup>He kept below 1.1 K and diffuse in transport channel towards experimental area.

The temperature of the isopure <sup>4</sup>He, exposed to 10 W of beam heat load is kept by the <sup>3</sup>He cryostat connected and the heat exchanger.






- Six welded aluminium layers
  - 1. Superfluid He vessel
  - 2. He/D2 vacuum separation (able to withstand 21 bar D2 explosion pressure) and 20 K thermal shield
  - 3. Inner LD2 vessel wall
  - 4. Outer LD2 vessel wall
  - 5. 100 K thermal shield
  - 6. Outer vacuum vessel
- Layer 1 completed and UCN storage lifetime validated at LANL in December 2020 (<a href="https://doi.org/10.1016/j.nima.2023.168106">https://doi.org/10.1016/j.nima.2023.168106</a>)
- Layer 6 welding and installation completed April 2024









- 4He pumping system to reach 1.6 K
- 3He pumping system to reach 0.8 K
- Designed to cool 3He to ~0.8 K with 10 W heat load
- Performance in 2024: ~0.9 K with 10 W heat load






The 4K pot is filled by the <sup>nat</sup>He purifier with a ~40 l/h capability.


The 1K pot and 3He are cooled down by the 3 sets of Busch pumps.

	Mass Flow [g/s]	Flow [m³/h]	Vacuum [Torr]
<sup>3</sup> He	0.57	4650	2.5
<sup>nat</sup> He	0.607	1900	4.83






- Cold liquid <sup>3</sup>He drops into a pot
- The boiling <sup>3</sup>He in the pot removes heat from the superfluid <sup>4</sup>He via a copper heat exchanger (HEX1)
- Boiling <sup>3</sup>He is pumped away by very big pumps






# June 2025 UCN production tentative

- 390 L of heavy water (546 L at full capacity)
- No LD<sub>2</sub>
- 27 cm of isopure <sup>4</sup>He (36 cm at full capacity)









### Scintillating stacks Lithium detector:

- $^{6}\text{Li} + n \rightarrow \alpha(2.05\text{MeV}) + t(2.73\text{MeV})$
- The upper layer is 60  $\mu$ m thick depleted <sup>6</sup>Li glass (0.01 %), and the lower layer is 120  $\mu$ m thick doped <sup>6</sup>Li (95 %) glass. Ensure energy deposition in scintillating glass.
- Fast signal 6 ns rise time 55 ns fall time allows for MHz detection.
   89.7 % efficiency






Friday June 13<sup>th</sup>, 2025 10:34 am







arXiv:2509.02916 [nucl-ex]

- •Vapor pressure in tail section consistent with superfluid isopure <sup>4</sup>He temp of 0.9-1.1K
- Beam heat load matched estimation



### Example Data after 60s proton irradiation time





Simulation package includes:

- MCNP of the source geometry
- UCN production
- PENTrack for UCN transport

Measurement in reasonable agreement with simulations.

Source storage lifetime ~25-30 seconds.


First UCN production does not show saturation at high beam current! Maybe sources like ours can support higher neutron fluxes than anticipated.



### **CONCLUSION**

- The TUCAN collaboration produced its first UCN in June 2025.
- First results are very promising and more cryogenic study need to be done to fully understand them.
- The source will be completed and fully commissioned by the end of the year (x76 UCN production).
- The nEDM experiment will be built in 2026 and commissioned in 2027.





The experimental area will be open to users.







March 2025 Collaboration Meeting, TRIUMF







































