

DarkSide computing TDR

Yann Coadou

CPPM Marseille

DS group meeting
CPPM, 4 July 2024





Table of contents



| | | | |
|---|----|-------------------------------------|----|
| 1. Introduction | 1 | 5. Simulation | 24 |
| 1.1. Physics goals | 1 | 5.1. Simulation data formats | 24 |
| 1.2. System requirements | 2 | 5.2. Physics processes | 25 |
| 1.3. Computing model | 3 | 5.3. Simulation pipeline | 26 |
| 1.4. Architecture | 4 | 5.4. CPU and storage requirements | 27 |
| 2. Raw data | 4 | 6. Computing model | 27 |
| 2.1. Operating modes of the detector | 4 | 6.1. Architecture | 27 |
| 2.2. Types of raw data | 6 | 6.2. Databases | 29 |
| 2.3. Data streams | 7 | 6.3. Data management | 30 |
| 2.4. Slow control information | 7 | 6.4. Data distribution | 31 |
| 2.5. Detector conditions | 8 | 6.5. Data access | 32 |
| 2.6. Data format | 9 | 6.6. Data processing | 32 |
| 2.7. Storage requirements | 10 | 6.7. Reconstruction scheduling | 33 |
| 2.8. Data transfer | 11 | 6.8. Simulation scheduling | 33 |
| 2.9. Data flow | 12 | 6.9. User analysis | 34 |
| 3. Raw data processing | 12 | 7. Software development | 35 |
| 3.1. Reconstruction | 12 | 7.1. Software components | 35 |
| 3.2. Types of reconstructed data | 14 | 7.2. Software releases | 35 |
| 3.3. Reconstruction pipeline | 15 | 7.3. Development workflow | 36 |
| 3.4. Calibration and monitoring pipelines | 16 | 7.4. Computing model implementation | 37 |
| 3.5. CPU requirements | 18 | 8. Organization and planning | 37 |
| 3.6. Storage requirements | 20 | 8.1. Development of the system | 37 |
| 4. User analysis | 22 | 8.2. Commissioning | 39 |
| 4.1. From reconstructed data to physics results | 22 | 8.3. Operation and maintenance | 40 |
| 4.2. Typical workflow | 23 | 8.4. Financial requests | 41 |

Section managers

■ Davide Franco

■ Marco Rescigno

■ Maria Adriana Sabia

■ Paolo Agnes

■ Pierre-André
Amaudruz

■ Saverio D'Auria

■ Timothée Hessel

■ Valerio Ippolito



Operating modes of detector

- **WIMP search mode:** most of the time. 88 Hz from ^{39}Ar β activity in TPC. Additional rate from SiPM dark counts: 40 Hz per each of the 2720 readout channels
- **Laser calibration mode:** PDM calibration by irradiating TPC with fibers in single-PE regime
- **Random trigger calibration mode:** unbiased PDM noise measurement and digitiser level hit finder efficiency
- **External calibration mode:** radioactive sources in calibration pipes or dissolved in LAr
- **Random waveform monitoring mode:** random acquisition of waveform chunks (length of single-PE signal, $5.6 \mu\text{s}$)

Data streams

- Main stream (WIMP search mode) at about 60 MB/s
- Additional fast online event identification to control data throughput (selection, prescaling) and flag supernova candidates for SNEWS alerts (under investigation)

| Context | Content type | Content |
|-----------------|--------------|-------------------------------|
| slice header | int4 | slice start marker |
| slice header | int4 | run type |
| slice header | int20 | run number |
| slice header | int4 | data quality flags |
| slice header | int32 | slice ID |
| slice header | int32 | timestamp |
| slice header | int32 | slice end marker |
| slice header | int32 | number of blocks in the slice |
| block specifier | int16 | block element type |
| block specifier | int16 | block element version |
| block specifier | int32 | block element multiplicity |
| block specifier | int32 | block element size |

| Context | Content type | Content |
|-----------------|-------------------------|---|
| block specifier | $2 \times \text{int32}$ | TPC ZLE block specifier |
| block specifier | $2 \times \text{int32}$ | TPC hit block specifier |
| block specifier | $2 \times \text{int32}$ | IV hit block specifier |
| block specifier | $2 \times \text{int32}$ | OV hit block specifier |
| block specifier | $2 \times \text{int32}$ | sum of the top waveforms block specifier |
| block specifier | $2 \times \text{int32}$ | sum of the bottom waveforms block specifier |

| Context | Content type | Content |
|-----------------------|--|-----------------------------|
| ZLE block | /int16 | ZLE channel |
| ZLE block | int16 | number of hits in ZLE |
| ZLE block | float32 | ZLE time |
| ZLE block | float32 | ZLE integral |
| ZLE block | float32 | ZLE length |
| Hit block | float32 | hit time |
| Hit block | float32 | hit charge |
| Summed waveform block | $N_{\text{samples}} \times \text{float32}$ | sum of the top waveforms |
| Summed waveform block | $N_{\text{samples}} \times \text{float32}$ | sum of the bottom waveforms |




2. Data transfers



- Not that straightforward given LNGS location
- On paper:
 - Ad-hoc optical fiber connecting underground LNGS to surface, planned at 10 Gb/s
 - 10 Gb/s link from external LNGS facility to Italian GARR computing network (“soon” upgraded to 100 Gb/s)
 - Via GARR, 8–10 Gb/s connection to CNAF
- Real life tests: 2 Gb/s from external LNGS to CNAF
- Weak point: underground to external LNGS (not considered critical by labs. . .)
⇒ underground storage buffer to stay offline for more that a week (100 TB)

- Reconstruction: algorithms applied to raw data to derive nature (NR or ER), energy, topology, etc.
- Staged reconstruction planned (not fully ready yet) to speed up reprocessing
- **Time slice** = time series of PE-induced hits
- First step: **Bayesian blocks** (data chunks with constant rate)
- Second step: **basic variables** for “easy” pulse classification (number of hits, charge integration, prompt component)
- **Refined reco**: xy and z position, dealing with outliers
- **Event building**: association of scintillation and ionisation pulses



| Task | CPU pledge (cores) | Disk | Tape |
|------------------------|--------------------|--------|--------|
| Raw data | | 20 PB | 20 PB |
| Prompt data processing | 100 | 75 TB | 75 TB |
| Reprocessings | 3000 | 300 TB | < 1 PB |
| User analysis | 300 | 300 TB | |
| MC simulation | 500 | 2 PB | 2 PB |
| Overall | 1500 | 20 PB | 20 PB |

- Various assumptions, e.g. reprocessing of early stages every six months but turnaround of one week of refined reco in early stages, averaged to four months in TDR
- Includes dealing with calibration (2 weeks for ER, 36 days for NR)
- Considers that users will not analyse full 70 TB each time (event skimming/slimming), especially true as time goes on
⇒ User analyses considered a minor contribution to computing resources



5. Simulation

- G4DS for tracking energy deposits and particle production
- Generation of scintillation signals (S1 full sim) in G4DS
- Generation of electroluminescence signal (S2) by fully tracking photons (G4DS, full-sim) or inferring light pattern for each energy deposit from light maps (dslab, fast-sim)
- Simulation of electronics response in PDM
- Reconstruction (as on real data)

6. Databases

- Storage of slow control, detector conditions, calibration constants, bookkeeping of data and simulation datasets, and of user jobs, authentication
- Not much detail yet



6. Data management/distribution/processing



- Data management: potentially rucio (from ATLAS originally)
- Distribution: CNAF foreseen. Decide this year if we could propose another site like CC-IN2P3
- Processing: considering DIRAC, or PanDA (from ATLAS originally)



7. Software



- Relies of python packages like numpy and dask, accelerated with high-performance just-in-time compilation with numba
- Analysis format: ROOT TTree
- Code managed in git, hosted at IN2P3 gitlab



| Milestone | When | Goal | Needs |
|--|----------|---|--|
| M1: Offline data challenge | Dec 2024 | Stress-test the pulse reconstruction with 10 h of simulated raw data | Pulse reconstruction software |
| M2: Release of computing TDR | Mar 2025 | Provide final assessment of needed resources for DarkSide computing | Estimation of pulse and event reconstruction performance |
| Computing prototype | Mar 2025 | Integrate simulation/reconstruction with prototype of data and workload management system | Data management and workload management pilots |
| M3: DAQ + offline data challenge | Jun 2025 | Test integration of vertical slice and computing prototype | Vertical slice setup, computing prototype |
| M4: DAQ + offline + DBs data challenge | Dec 2025 | Integrate computing system with its full input with the actual detector underground | DAQ operational underground at LNGS |
| M5: Commissioning | Dec 2026 | Commissioning of the computing system with the sealed detector | Detector ready |

| Risk | Probability | Impact | Mitigation |
|--|-------------|--------|---|
| Unavailability of data management system | Medium | High | Early implementation on the development phase, in synergy with CNAF. Disk buffer at LNGS allows one week to fix transient issues. |
| Unavailability of workload management system | Low | Medium | Early implementation. Availability of full data on a single computing site (CNAF) allows to resort to temporary backup solution such as HTCondor. |
| Unavailability of detector databases | Medium | Medium | Can export DB fragments as dataset metadata. |
| Unavailability of authentication system | Low | Low | Backup credentials for central production |
| Storage corruption | Low | Medium | Redundancy of data copies (disk/tape) |
| Interruption of network connection to/from LNGS | High | High | Disk buffer on DAQ farm, DB replicas |
| Data format insufficient for detector characterization/physics | Medium | Low | Flexible raw data format. Support for schema evolution in raw and processed data formats. |
| Limited person power | High | High | Periodic user, developer and support team training. Shared documentation. Usage of GitOps/DevOps paradigms for automation |