Einstein Telescope ET France







Ghada Mahmoud – Systems Engineer / Risk Manager - ETO Project Office ghada.mahmoud@apc.in2p3.fr

When were Risk Studies performed in ET by the ETO PO?

Phase	Risk-Related Activity									
2024 – 2025	 ETO PO General Risk Campaign (starting June 2024): First General structured, collaborative risk campaign across technical groups (All ISB Subsystems: Interferometer Group, Optics Group, Suspension Group, Vacuum and cryogenics Group, ANM Group; and Engineering Department) It Delivers the First Full Risk Register for ET TRL Assessments 									
2025	 Continuing with the ETO PO General Risk Campaign: Review, other Stakeholders ETO Taskforce: TRL assessments Comparative risk studies between different Configurations of 2L and Triangle Geometries Flexibility (DSM) and Penalty of change (trade-off analysis between designs and cost impact evaluation) studies 									
Now	 Reviewing Risk Register + Taking actions; Also learning lessons Cross-cutting risk integration (identifying, analyzing, and managing risks that affect multiple subsystems, teams, or domains simultaneously) Integrating, Risks into MBSE (Jama and 3DX) Final Risk Management Plan with Lesson learned + Risk Report and Risk Registers 									



Outcome of the ETO PO General Risk Campaign

- More than 200 risks (mostly technical) identified and assessed across major subsystems (Interferometer, Active Noise Mitigation (ANM), Vacuum & Cryogenics, Optics, Suspension, Engineering Department)
- Risk identification was strongly collaborated with technical and scientific teams, ensuring ownership and technical accuracy.
- Moving from Assessing risks only to transforming **risk mitigations into real design enabler**.



Example on a Technical Risk from the ETO PO General Campaign and its impact on trade off

Risk Description:

A risk that the required specifications for the ET-LF test mass (TM) substrates may not be met.

ET-LF lack of substrate availability in suitable dimensions (actually 45 cm diameter) and with suitable optical properties.

Factor	Value
Severity	5 /5
Likelihood	5/5
Overall Risk	High

Cause:

The test mass substrates must possess both large dimensions and exceptional optical characteristics, including low optical absorption and low birefringence.

At present, materials that meet these criteria (silicon and sapphire) are not available at the required **size** and **quality.**Birefringence is a particularly significant challenge for sapphire.

Impact:

If the necessary substrates cannot be procured, the ET-LF detector may not be constructed according to its current design.

This would compromise its ability to meet scientific objectives, potentially requiring reductions in beam size and TM mass.

Suggested Mitigations:

- Continue parallel R&D efforts into both silicon and sapphire substrates ?!!!! → We may move start building/ highlighting PROJECT Requirements such as ET labs for developing R&D for ET
- Investigate the viability of other materials designs.
- Conduct trade-off studies to assess the feasibility of tolerating higher optical absorption levels ?!!!! → Scope
- Explore alternative optical layouts that are compatible with smaller mirror sizes → Configuration



Impacts analysis - trade off: example on a cost variation scenario

Example:

If we suggest reducing the diameter of LF TM from 45 cm to 35 cm (to give more time for developing R&D) then the arm length will be maximum 10 KM

→ we can't construct a 2L configuration for ET with 15 KM armlength (we will be able to construct 10 KM 2L Configuration instead) and the triangle ET Configuration of 10 KM armlength won't be not affected.

Example on the cost change:

- Cost Impact: Cost difference of possible 24,98 % reduction of the excavated volumes with respect to the 2025 2L Configuration (15 KM) one.
- The triangle cost remains unchanged.

The trade off should take into account the impact of the length reduction on the scientific scope, also on the upgradability.




Rik Analysis using Excel Sheets

lat parr	Cunfiqu ration	Rirk ID	ID HL	Graup	₩P	Praduct	Deta	Rirk Title	Rirk Demein	Rirk Cours	Rirk Impact	Suggested mitigation	Severity befure mitigation (Triangle)	Likelihund befure mitigatiun (Triangle)	Criticality (Triangle)	Severity before mitigation (L Shape)	d befure mitigatin m (L	Oritical ity (L Skape)	Comments	Rirk Erceletion Laval	Kurk Ounership (in cullaburatio	Rick Ounership WP	Severit	l Likelihu ud	el Critice lity (Severit Lil	l I kaliku Critical I (L ity (L
	d	R.Op.S c.	1	Optics	Input Output Optics		1\$.1.2 \$ 2 5	Limito-d prugrozz un 100 dozign	Schedule	larufficient persus puwer	Dolay in doziqu by at loart a yoar	Increase FTE cummitments to 100 from 0.1 FTE to several FTE. Have ton cur-chairs of the group, with at least one of them with significant FTE cummitment.	4	5	20			•		Erceleted tu Henegomont	ЕТО				•		
	d	R.Op.T c.	1	Optics	Input Output Optics		1\$.1.2 0 2 5	Cametroiste an eatin batusan cavitise langth	Technical		Ha caurdinatiun batusan Optics and Interferameter divirium	Define the interferometer control stratogy, edject the length of the different covities to fit that stratogy, and edjust the position of the coverar by factors of maters to respect the needed relations.	5	•	28			•	Length of the orm certity, of the power recycling early, and rigant recycling early; and length of the second (or may) input under cleaner have integer relation. The lengths need the multiple deposition in rune ceres). This is maded as the refin- frequency fields here the right remains a mail- resement conditions.	Ercalated tu Management					•		
	d	R.Op.T c.	z	Optics	Care Optics			ET-LF lock of substrato evailshility in suitable dimensions and uith suitable uptical properties	Tachnical	Test mass substrates with large dimensimas, hus mytical absurption and hus birefringance are required. Currently large samuch and pure causely elitemizaphic in ant available. Birefringance is an izrue far capphire.	LF could not be constructed in itr current design (redcuced beam	Continued R&D of silicon and supphire in parallel. Tredu-off studies of the offect of accepting higher subtracts optical description. Investigate mulfifed aptical layout compatible with smaller mirror sizes, layoutique comparite text mare designs.	5	5	25			•	TRL (International Callaburation CE)	Ercalated tu Project Steering Cummittee					•		
	d	R.Op.T c.	3	Optics	Cura Optics			ET-LF & ET-HF thermal anire/aptical abstraction and compliance	Technical	Failure to meet costing thermal naire target or aptical absorption target.		BED us costing meterials and costing during (more human power maybe f Budget)	3	4	12			•	A lack of time to invast more in ET & There have the model appariance, they don't have enough time of Experienced Comparisons of the experience of Experienc	Toem- Henegod					•		•
	d	R.Op.T		Optics	Care Optics			ET-LF & ET-HF custing uniformity/defect nun- cumpliance	Tochnical	Putontial izzaoz uith upzcaliną cuatinąz tu largor diamtorz (unifarmity d pnint dofoctr). Dolay in dovolupiną nou mirrur praductiun facility (tun mirrurz at unco).	scattering (defects),	R&D on uprcaling conting deparition (more human power maybe f Budget) (Hight confidence to queronty the Results)	3	•	12			•	A lock of time to invest more in ET of Thery have the seeded experience, they don't have enough time of Experienced people in Consting for the mirrors are needed (2 engineers of scientists are enough, if more it's better) of	Team- Hanaged					•		•
	d	R.Op.T	5	Optics	Cura Optics			Ico formation in ET-LF	Tachnical	Grauth of ice layers on test mass surface due to cryopumping of mater vapour from interferometer arms.	Increased uptical absurption and thermal noire. Altered mirror reflectivity	Batter vacuum. Derign of better buffler etc. R&D of systems to remove ice e.g. heating mirror periodically # CO2 larer ablation of ice layer.	3	3	,			•		Inter-Group Culleburatio					•		
	d	R.Op.T c.	٠	Optics	Cura Optics			Demego of a Tort- Mars/Boomsplittor	Technical	Demoge during the installation of the surpensions on the transfer to the transfer to the tours. Failure of the cuating	Shutdaun fur >2 years fur the inteferumeter and extra cart.	Spare parts roady un the shelf.	•	2	*			•	Such a damage accured in the part in Virga because of the break of a vieupart.	Inter-Graup Cullaburatio					•		
•	<i< th=""><th>R.Op.5 c.</th><th>2</th><th>Optics</th><th>Cure Optics</th><th></th><th></th><th>Tuu lunq delivery time fur the Test-Mass/Beamsplitter</th><th>Schodulo</th><th>Blank manufacturing Pulirhing Guatina Blank pruduction is an onorgy</th><th>Dalay Hasa increase of</th><th>Start the supply in the early steps of the construction. Update regularly the lead time from vendors.</th><th>3</th><th>3</th><th>,</th><th></th><th></th><th></th><th>Pulirhing cumpanies have currently lead times of 2 years for a couple of The price of Energy is</th><th>Team- Hanaged</th><th></th><th></th><th></th><th></th><th></th><th></th><th>•</th></i<>	R.Op.5 c.	2	Optics	Cure Optics			Tuu lunq delivery time fur the Test-Mass/Beamsplitter	Schodulo	Blank manufacturing Pulirhing Guatina Blank pruduction is an onorgy	Dalay Hasa increase of	Start the supply in the early steps of the construction. Update regularly the lead time from vendors.	3	3	,				Pulirhing cumpanies have currently lead times of 2 years for a couple of The price of Energy is	Team- Hanaged							•
	<i< th=""><th>R.Op.F</th><th>1</th><th>Optics</th><th>Cura</th><th></th><th></th><th>Increase of the price for the</th><th>Financial</th><th>CONTORING PERCOSES</th><th>the total cort</th><th></th><th>4</th><th>4</th><th>16</th><th></th><th></th><th><u>اب</u>ا</th><th>increasing with the years I we</th><th>Erceleted to</th><th>_</th><th>L</th><th></th><th></th><th></th><th></th><th></th></i<>	R.Op.F	1	Optics	Cura			Increase of the price for the	Financial	CONTORING PERCOSES	the total cort		4	4	16			<u>اب</u> ا	increasing with the years I we	Erceleted to	_	L					
•	•		Para	meters	Ri	sk Re	gister	Dashboards	Opt	tics Risk Register	Optics	Parameters V&C	Parame	ters	V&C Ri	sk Regi	ster	Qua	intitative Risk Ass	essment	(+)	4					




Rik Analysis within MBSE (JAMA)






Risk Analysis within MBSE



Title	Type of Risk	Impact	Probability	Rating	Severity	Affected Items	Risk Rating Goal	Action Plan	Abatement Plan		
A Handling of Hea	Security	4	3	12	3-High	Vacuum Beam Pipe	2	Avoid	Provide regul		
A Confined Space	Security	4	3	12	3-High	Vacuum Beam Pipe	3	Control	Implement stri		
	Technical	3	3	9	2-Medium	Vacuum Beam Pipe	3	Avoid	Rigorous testi		
Fire Hazards	Security	4	3	12	3-High	Vacuum Beam Pipe	3	Control	Implement the		



Risk Analysis within MBSE





Lessons Learned

- Shorter assessment cycles = more agility and faster decisions.
- Effective communication/documentation is key for alignment.
- Continuous stakeholder feedback strengthens buy-in and outcomes.
- MBSE integration enhances traceability and long-term learning.



Conclusion

Our Last Risk Activities:

- Enabled direct engagement with stakeholders to identify, assess, and mitigate project risks.
- Provided our first full experience, teaching valuable lessons.
- We now have data-driven insights to guide risk actions and decisions.
- Future campaigns will emphasize broader stakeholder involvement, ensuring diverse and comprehensive risk perspectives.
- A more adapted and tailored risk management plan (RMP) aligned with project-specific and stakeholder needs



Einstein Telescope ET France



ET- FRANCE

Thank You!